


STATE OF MISSOURI
DEPARTMENT OF NATURAL RESOURCES
MISSOURI AIR CONSERVATION COMMISSION



PERMIT BOOK

PERMIT TO CONSTRUCT

Under the authority of RSMo 643 and the Federal Clean Air Act the applicant is authorized to construct the air contaminant source(s) described below, in accordance with the laws, rules and conditions as set forth herein.

Permit Number: **1 2 2 0 0 6 - 0 0 6** Project Number: **2006-09-007**
PORT-0467
Owner: **Doss & Harper Stone Co., Inc.**
Owner's Address: **P.O. Box 888, West Plains, MO 65775**
Installation Name: **Doss & Harper Stone Rock Crushing Port - 0467**
Installation Address: **County Road E-201, Alton, MO 65606**
Location Information: **Oregon County County, S26, T23N, R4W**

Application for Authority to Construct was made for:


The modification of an existing portable rock crushing plant. Rock is processed through 1 crusher(s), 1 screen(s), and 3 conveyor(s). The portable rock crushing plant has a maximum hourly design rate (MHDR) of 221.0 tons per hour (tph). Best Management Practices will be used to control fugitive emissions from storage piles and haul roads. This review was conducted in accordance with Section (6), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*.

Standard Conditions (on reverse) are applicable to this permit.

Standard Conditions (on reverse) and Special Conditions (listed as attachments starting on page 2) are applicable to this permit.

DEC - 8 2006

EFFECTIVE DATE


DIRECTOR OR DESIGNEE
DEPARTMENT OF NATURAL RESOURCES

STANDARD CONDITIONS:

Permission to construct may be revoked if you fail to begin construction or modification within two years from the effective date of this permit. Permittee should notify the Air Pollution Control Program if construction or modification is not started within two years after the effective date of this permit, or if construction or modification is suspended for one year or more.

You will be in violation of 10 CSR 10-6.060 if you fail to adhere to the specifications and conditions listed in your application, this permit and the project review. Specifically, all air contaminant control devices shall be operated and maintained as specified in the application, associated plans and specifications.

You must notify the Air Pollution Control Program of the anticipated date of start up of this (these) air contaminant source(s). The information must be made available not more than 60 days but at least 30 days in advance of this date. Also, you must notify the Department of Natural Resources Regional Office responsible for the area within which you are located within 15 days after the actual start up of this (these) air contaminant source(s).

A copy of this permit and permit review shall be kept at the installation address and shall be made available to Department of Natural Resources' personnel upon request.

You may appeal this permit or any of the listed Special Conditions as provided in RSMo 643.075. If you choose to appeal, the Air Pollution Control Program must receive your written declaration within 30 days of receipt of this permit.

If you choose not to appeal, this certificate, the project review, your application and associated correspondence constitutes your permit to construct. The permit allows you to construct and operate your air contaminant source(s), but in no way relieves you of your obligation to comply with all applicable provisions of the Missouri Air Conservation Law, regulations of the Missouri Department of Natural Resources and other applicable federal, state and local laws and ordinances.

The Department of Natural Resources has established the Outreach and Assistance Center to help in completing future applications or fielding complaints about the permitting process. You are invited to contact them at 1-800-361-4827 or (573) 526-6627, or in writing addressed to Outreach and Assistance Center, P.O. Box 176, Jefferson City, MO 65102-0176.

The Air Pollution Control Program invites your questions regarding this air pollution permit. Please contact the Construction Permit Unit at (573) 751-4817. If you prefer to write, please address your correspondence to the Air Pollution Control Program, P.O. Box 176, Jefferson City, MO 65102-0176, attention Construction Permit Unit.

Page No.	2
Permit No.	
Project No.	2006-09-007

GENERAL SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

The special conditions listed in this permit were included based on the authority granted the Missouri Air Pollution Control Program by the Missouri Air Conservation Law (specifically 643.075); by the Missouri Rules listed in Title 10, Division 10 of the Codes of State Regulations (specifically 10 CSR 10-6.060); by 10 CSR 10-6.060 paragraph (12)(A)10. "Conditions required by permitting authority"; by 10 CSR 10-6.010 "Ambient Air Quality Standards" and 10 CSR 10-6.060 subsections (5)(D) and (6)(A); and by control measures requested by the applicant, in their permit application, to reduce the amount of air pollutants being emitted, in accordance with 10 CSR 10-6.060 paragraph (6)(E)3. Furthermore, one or more of the Subparts of 40 CFR Part 60, New Source Performance Standards (NSPS), applies to this installation.

1. **Portable Equipment Identification Requirement**
To assure that each component is properly identified as being a part of this portable rock crushing plant, (PORT-0467) Doss & Harper Stone Rock Crushing Port - 0467 shall provide and maintain suitable, easily read permanent markings on each component of the plant. These markings shall be the equipment's serial number or a company assigned identification number that uniquely identifies the individual component. These identification numbers must be submitted to the Air Pollution Control Program no later than 15 days after start-up of the portable rock crushing plant.
2. **Relocation of Portable Rock Crushing Plant**
 - A. A complete "Portable Source Relocation Request" application must be submitted to the Air Pollution Control Program prior to any relocation of this portable rock crushing plant.
 - 1.) If the portable rock crushing plant is moving to a site previously permitted, and if there are no other new plants at the site, then the application must be received by the Air Pollution Control Program at least seven (7) days prior to the relocation.
 - 2.) If the portable rock crushing plant is moving to a new site, or if there are other plants or equipment at the site that have not been evaluated for concurrent operation, then the application must be received by the Air Pollution Control Program at least twenty-one (21) days prior to the relocation. The application must include written notification of any concurrently operating plants.
3. **Record Keeping Requirement**
The operator(s) shall maintain all records required by this permit for not less than five (5) years and shall make them available to any Missouri Department of Natural Resources' personnel upon request.
4. **Superseding Condition**
The conditions of this permit supersede all special conditions found in the previously issued construction permit(s) from the Air Pollution Control Program (Permit Number 072002-015) and all of its amendments and relocations.

Page No.	3
Permit No.	
Project No.	2006-09-007

SITE-SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

Site ID No.: 777-0467
Site Name: Oregon County Quarry
Site Address: County Road E-201, Alton, MO 65606
Site County: Oregon County County, S26, T23N, R4W

1. **Best Management Practices**
Doss & Harper Stone Rock Crushing Port - 0467 shall control fugitive emissions from all of the haul roads and stockpiles at this site by performing *Best Management Practices*, which include the usage of paving, chemical dust suppressants, or documented watering. These practices are defined in Attachment AA.
2. **National Ambient Air Quality Standards (NAAQS) Limitation for Particulate Matter Less Than Ten Microns in Diameter (PM₁₀)**
 - A. The operator(s) for Doss & Harper Stone Portable Rock Crushing Plant Port - 0467 shall ensure, while operating at this site, that the ambient impact of PM₁₀ at or beyond the nearest property boundary does not exceed 150 µg/m³ in any 24-hour period, in accordance with the Federal NAAQS requirements (40 CFR 50.6).
 - B. The total daily ambient impact of PM₁₀ at this site shall include the combined impact of the Doss & Harper Stone Portable Rock Crushing Plant Port - 0467 and any ambient background concentration from installation or equipment located on the same site as the Doss & Harper Stone Portable Rock Crushing Plant Port - 0467
 - C. To demonstrate compliance with special condition 2A, the operator(s) shall maintain a daily record of material processed.
 - 1.) During concurrent same owner operations use Attachment A-1 or other equivalent form(s) for this purpose.
 - 2.) During concurrent separate owners operations use Attachment A-2 or other equivalent form(s) for this purpose.
 - 3.) During concurrent same and separate owners operations use Attachment A-2, or other equivalent form(s) for this purpose
3. **Moisture Content Testing Requirement for Inherent Moisture Content**
 - A. The inherent moisture content of the rock will reduce particulate emissions. Doss & Harper Stone Rock Crushing Port - 0467 claimed the inherent moisture content of the processed rock to be greater than or equal to 1.5 wt.%, which shall be verified by testing.
 - B. Testing shall be conducted according to approved methods, such as those prescribed by the *American Society for Testing Materials (ASTM D-2216 or C-566)*, EPA AP-42 Appendix C.2, or other method(s) approved by the Director. The first test shall be no later than 45 days after startup. Testing shall be conducted at least once every two years after the initial test, during the months of June through September, while the portable rock crushing plant is active at this site.
 - C. Test samples shall be obtained before processing (before entering the Primary Crusher) and after processing (prior to load-in to bins and/or storage piles). During the sample processing run only, any spray devices shall be turned off during the processing from which test samples are obtained. The written analytical report shall include the raw data and moisture content (wt.%) of each sample, the test date, and the original signature of the individual performing the test. Within 30 days of completion of the required tests, the report shall be filed on-site or at the Doss & Harper Stone Rock Crushing Port - 0467 main office.
 - D. If the inherent moisture content result of the first test is less than 1.5 wt.%, a second test must be performed within 30 days. If the result of the second test is less than 1.5 wt.%, Doss & Harper Stone Rock Crushing Port - 0467 shall apply for a new construction permit to account for the revised information or install wet spray devices on the affected units.

Page No.	4
Permit No.	
Project No.	2006-09-007

SITE-SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

4. **Restriction on Process Configuration of Primary Emission Point(s)**
The maximum hourly design rate of the plant is equal to the sum of the design rate(s) of the primary emission point(s). Bypassing the primary emission point(s) for processing is prohibited.
5. **Restriction on Minimum Distance to Nearest Property Boundary**
The primary emission point of the portable rock crushing plant, which is the primary crusher, shall be located at least 400 feet from the nearest property boundary whenever it is operating at this site.
6. **Restriction on the Use of Diesel Engine(s)**
The portable rock-crushing plant shall not use its diesel engine(s) for any purpose other than powering its equipment during production.
7. **Record Keeping Requirement**
The operator(s) shall maintain all records required by this permit for not less than five (5) years and shall make them available to any Missouri Department of Natural Resources' personnel upon request.
8. **Reporting Requirement**
The operator(s) shall report to the Air Pollution Control Program Enforcement Section, P.O. Box 176, Jefferson City, MO 65102, no later than ten (10) days after any exceedances of the limitations imposed by this permit.
9. **Superseding Condition**
The conditions of this permit supersede all special conditions found in the previously issued construction permit(s) from the Air Pollution Control Program (Permit Number 022005-012) and all of its amendments and relocations

TECHNICAL REVIEW OF APPLICATION FOR AUTHORITY TO CONSTRUCT

PROJECT DESCRIPTION

Doss & Harper Stone Company submitted their application to modify their existing permit number 072002-015 to implement Best Management Practices and to allow concurrent operations at the site.

Rock, composed of non-metallic minerals, is drilled/blasted, loaded into haul trucks, and transported to processing. Rock is processed through feeder(s), crusher(s), screen(s), conveyor(s), and bin(s). Processing equipment is powered with diesel engine(s). The emission points are listed in the attached spreadsheet summary. This installation is not on the List of Named Installations [10 CSR 10-6.020(3)(B), Table 2]. The installation is located in Oregon County County, an attainment area for all criteria air pollutants.

The stationary rock-crushing plant is permitted to operate under the following four (4) scenarios.

- Solitary Operation: No other plants can operate at the site.
- Concurrent, Same Owner: The plant can operate with other asphalt, concrete, or rock-crushing plants owned by Doss & Harper Stone Co. Inc.
- Concurrent, Separate Owners: The plant can operate with other asphalt, concrete, or rock-crushing plants owned by other companies.
- Concurrent, Same and Separate Owners: The plant can operate with other asphalt, concrete, or rock-crushing plants owned by Doss & Harper Stone Co. Inc. at the same time as asphalt concrete, or rock-crushing plants owned by other companies.

EMISSIONS EVALUATION

Criteria air pollutants will be emitted from this operation. The main air pollutant of concern is PM₁₀. The potential emissions were calculated from the maximum hourly design rate (MHDR) of the equipment, appropriate emission factors, control device efficiencies, and the limiting operating hours at MHDR. The sources of the emission factors and control efficiencies are listed in the section "Permit Documents". Based on the conditioned potential emissions, the operation is considered a minor source under 10 CSR 10-6.060 section (6).

Table 2: Emissions Summary (tons per year)

Air Pollutant	Regulatory De Minimis Levels	Existing Potential Emissions	Existing Actual Emissions (year2005)	Potential Emissions of the Application	**New Installation Conditioned Potential	Emission Factor (lb/ton)
PM ₁₀	15.0	N/A	N/A	29.15	N/A	N/A
SO _x	40.0	N/A	N/A	0.86	N/A	N/A
NO _x	40.0	N/A	N/A	13.05	N/A	N/A
VOC	40.0	N/A	N/A	1.07	N/A	N/A
CO	100.0	N/A	N/A	2.81	N/A	N/A
HAPs	10.0/25.0	N/A	N/A	0.01	N/A	N/A

Note: N/A = Not Applicable.

** Conditioned potential based on De minimis limit. Other pollutants proportionately reduced.

AMBIENT AIR QUALITY IMPACT ANALYSIS

Screening tools were used to evaluate the ambient air impact of the hourly emissions from this operation. The ambient impact was evaluated at a distance of 400 feet to the nearest property boundary. The ambient impact at this site shall not exceed the National Ambient Air Quality Standard (NAAQS) of 150 µg/m³ of PM₁₀ at or beyond the nearest property boundary in any single 24-hour period. The screening tools were used to develop an ambient impact factor for the portable rock crushing plant. This ambient impact factor is incorporated into the daily record-keeping table, Attachment A-1, A-2.

For sources agreeing to use Best Management Practices (BMPs), as defined in Attachment AA, haul roads and stockpiles are not modeled with screening tools. Instead, they are addressed as a background level of 20 µg/m³

of PM₁₀. To ensure conformity with NAAQS, the remaining process emissions are limited to an impact of less than 130 µg/m³ of PM₁₀ at or beyond the nearest property boundary.

Doss & Harper Stone Portable Rock Crushing Plant Port - 0467 is permitted to operate under four (4) scenarios. The PM₁₀ ambient impact record keeping requirements for each scenario are as follows

- Solitary Operation: No Record Keeping for this scenario
- Concurrent, Same Owner: The Doss & Harper Stone Portable Rock Crushing Plant Port - 0467 must track its own daily PM₁₀ ambient impact **AND** the daily PM₁₀ ambient impact of other plants that are owned by Doss & Harper Stone Co. Inc.. Attachment A-1, or equivalent form(s), can be used for this purpose.
- Concurrent, Separate Owners: Doss & Harper Stone Portable Rock Crushing Plant Port - 0467 shall decrease its production to limit its daily PM₁₀ ambient impact to below 77.0 µg/m³. The plants owned by the other companies will then be allowed the remaining balance of 53.0 µg/m³. No record keeping for this scenario
- Concurrent, Same and Separate Owners: Doss & Harper Stone Portable Rock Crushing Plant Port - 0467 must track its own daily PM₁₀ ambient impact and that of any other plants owned by Doss & Harper Stone Co. Inc. to ensure that the combined daily PM₁₀ ambient impact from all plants is below 77.0 µg/m³. Attachment A-2, or equivalent form(s), can be used for this purpose. The remaining balance of 53.0 µg/m³ can be used by the plants owned by the other companies

Table 3: Ambient Air Quality Impact Analysis of PM₁₀, 24-Hour Averaging Time

Operation	Ambient Impact Factor (µg/m ³ /ton)	Modeled Impact (µg/m ³)	*Background (µg/m ³)	NAAQS (µg/m ³)	Daily Production Limit (tons)
1. Solitary	0.007	37.32	20.00	150.00	5,304
2. Concurrent, Same Owner	0.007	**	20.00	150.00	**
3. Concurrent, Separate Owners	0.007	37.32	73.00	150.00	5,304
4. Concurrent Same and Separate Owners	0.007	**	73.00	150.00	**

*Background PM₁₀ level of 20.00 µg/m³ from haul roads and stockpiles and 53.0 µg/m³ from the operation of asphalt, concrete, or rock-crushing plants owned by other companies.

** The operator(s) must balance production among concurrently operating plants owned by Doss & Harper Plant. Such that NAAQS is not exceeded. The daily PM₁₀ ambient impact from other plants owned by Doss & Harper Co. Inc. can be obtained from the operators of these plants.

APPLICABLE REQUIREMENTS

The owner is subject to compliance with the following applicable requirements. The Missouri Air Conservation Laws and Regulations should be consulted for specific record keeping, monitoring, and reporting requirements.

- *Submission of Emission Data, Emission Fees and Process Information*, 10 CSR 10-6.110
- No Operating Permit is required for this portable rock crushing plant.
- *Restriction of Particulate Matter to the Ambient Air Beyond the Premises of Origin*, 10 CSR 10-6.170
- *Restriction of Emission of Visible Air Contaminants*, 10 CSR 10-6.220
- *Restriction of Emission of Odors*, 10 CSR 10-3.090
- *Restriction of Emission of Particulate Matter From Industrial Processes*, 10 CSR 10-6.400
- *Restriction of Emission of Sulfur Compounds*, 10 CSR 10-6.260
- 40 CFR Part 60 Subpart "OOO", *Standards of Performance for Nonmetallic Mineral Processing Plants*, of the New Source Performance Standards (NSPS)
- The National Emission Standards for Hazardous Air Pollutants (NESHAPs) and the currently promulgated Maximum Achievable Control Technology (MACT) regulations do not apply to the proposed equipment.

STAFF RECOMMENDATION

On the basis of this review conducted in accordance with Section (6), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*, I recommend this permit be granted with special conditions.

Samer Al-Shoukhi
Environmental Engineer

Date

PERMIT DOCUMENTS

The following documents are incorporated by reference into this permit:

- The Application for Authority to Construct form, designating Doss & Harper Stone Co., Inc. as the owner and operator of the installation.
- Environmental Protection Agency (EPA) AP-42, *Compilation of Air Pollutant Emission Factors; Volume I, Stationary Point and Area Sources, Fifth Edition*.
- Noyes Data Corp. book, Orlemann, et al. 1983, *Fugitive Dust Control*.
- EPA Factor Information Retrieval (FIRE) Version 6.21.
- Spreadsheet calculations of potential-to-emit and ambient impact.
- Southeast Regional Office Site Survey.
- Best Management Practices

**Attachment A-1: Daily Ambient PM₁₀ Impact Tracking Record
Doss & Harper Stone Rock Crushing Port - 0467
For Use During Concurrent Same – Owner Operation.**

Project Number: 2006-09-007
County, CSTR: Oregon County County (S26, T23N, R4W)
Primary Unit Size: 221 tph
Distance to Nearest Property Boundary: 400 feet

This sheet covers the period from _____ to _____ (Month, Day, Year) (Copy this sheet as needed.)

Date	Doss & Harper Stone Rock Crushing Port - 0467 PORT-0467 Project # 2006-09-007			Plant Name: Plant ID: Permit #:	Plant Name: Plant ID: Permit #:	Plant Name: Plant ID: Permit #:	³ Back-ground PM ₁₀ Level (µg/m ³)	⁴ TOTAL PM ₁₀ Level (µg/m ³)
	Daily Production (tons)	Ambient Impact Factor (µg/m ³ /ton)	¹ Daily PM ₁₀ Impact (µg/m ³)	² Daily PM ₁₀ Impact (µg/m ³)	² Daily PM ₁₀ Impact (µg/m ³)	² Daily PM ₁₀ Impact (µg/m ³)		
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	
		0.0070					20.00	

Note 1: The Daily PM₁₀ Impact (µg/m³) for the portable rock crushing plant is calculated by multiplying the Daily Production (tons) by the matching Ambient Impact Factor.
Note 2: The Daily PM₁₀ Impact (µg/m³) for the other plants owned by Doss & Harper Stone company. Can be obtained from the operator(s) of these plants. A value of zero (0) should be entered during solitary operations of the portable rock crushing plant.
Note 3: Background PM₁₀ Level (µg/m³) is from Haul Roads and Stockpiles.
Note 4: The TOTAL PM₁₀ Level (µg/m³) is calculated by summing the Daily PM₁₀ Ambient Impact(s) and the Background PM₁₀ Level. A TOTAL PM₁₀ Level of less than 150 µg/m³ in any 24-hour period indicates compliance.

Attachment A-2: Daily Ambient PM₁₀ Impact Tracking Record
Doss & Harper Stone Rock Crushing Port - 0467
For Use During Concurrent Operation With Plants Owned by Other Companies
Also For Use During Concurrent Same - Owner And Separate - Owner Operation

Project Number: 2006-09-007
 County, CSTR: Oregon County County (S26, T23N, R4W)
 Primary Unit Size: 221 tph
 Distance to Nearest Property Boundary: 400 feet

This sheet covers the period from _____ to _____ (Month, Day, Year) *(Copy this sheet as needed.)*

Date	Doss & Harper Stone Rock Crushing Port - 0467 PORT-0467 Project # 2006-09-007		Plant Name: Plant ID: Permit #:	Plant Name: Plant ID: Permit #:	Plant Name: Plant ID: Permit #:	³ Back-ground PM ₁₀ Level (µg/m ³)	⁴ TOTAL PM ₁₀ Level (µg/m ³)
	Daily Production (tons)	Ambient Impact Factor (µg/m ³ /ton)	¹ Daily PM ₁₀ Impact (µg/m ³)	² Daily PM ₁₀ Impact (µg/m ³)	² Daily PM ₁₀ Impact (µg/m ³)		
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	
		0.0070				73.00	

Note 1: The Daily PM₁₀ Impact (µg/m³) for the Portable rock crushing plant is calculated by multiplying the Daily Production (tons) by the matching Ambient Impact Factor.
 Note 2: The Daily PM₁₀ Impact (µg/m³) for other plants owned by Doss & Harper Stone company can be obtained from the operators of these plants. A value of zero (0) should be entered if there are no other plants owned by Doss & Harper Stone company at the site.
 Note 3: Background PM₁₀ Level (µg/m³) is from Haul Roads and Stockpiles and from the operations of asphalt, concrete, or rock-crushing plants owned by other companies.
 Note 4: TOTAL PM₁₀ Level (µg/m³) is calculated by summing the Daily PM₁₀ Ambient Impact(s) and the Background PM₁₀ Level. A TOTAL PM₁₀ Level of less than 150 µg/m³ in any 24-hour period indicates compliance

Attachment AA: Best Management Practices (BMPs)- Construction Industry Fugitive Emissions

Construction Industry Sites covered by the Interim Relief Policy shall maintain Best Management Control Practices (BMPs) for fugitive emission areas at their installations when in operation. Options for BMPs are at least one of the following:

For Haul Roads:

1. Pavement of Road Surfaces –
 - A. The operator(s) may pave all or any portion of the haul roads with materials such as asphalt, concrete, and/or other material(s) after receiving approval from the program. The pavement will be applied in accordance with industry standards for such pavement so as to achieve “Control of Fugitive Emissions¹” while the plant is operating.
 - B. Maintenance and/or repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall periodically water, wash and/or otherwise clean all of the paved portions of the haul road(s) as necessary to achieve control of fugitive emissions from these areas while the plant is operating.

2. Usage of Chemical Dust Suppressants –
 - A. The operator(s) shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to all the unpaved portions of the haul roads. The suppressant will be applied in accordance with the manufacturer’s suggested application rate (if available) and re-applied as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
 - B. The quantities of the chemical dust suppressant shall be applied, re-applied and/or maintained sufficient to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

3. Usage of Documented Watering –
 - A. The operator(s) shall control the fugitive emissions from all the unpaved portions of the haul roads at the installation by consistently and correctly using the application of a water spray. Documented watering will be applied in accordance with a recommended application rate of 100 gallons per day per 1,000 square feet of unpaved/untreated surface area of haul roads as necessary to achieve control of fugitive emissions from these areas while the plant is operating. For example, the operator(s) shall calculate the total square feet of unpaved vehicle activity area requiring control on any particular day, divide that product by 1,000, and multiply the quotient by 100 gallons for that day.
 - B. The operator(s) shall maintain a log that documents daily water applications. This log shall include, but is not limited to, date and volumes (e.g., number of tanker applications and/or total gallons used) of water application. The log shall also record rationale for not applying water on day(s) the plant is in operation (e.g., meteorological situations, precipitation events, freezing, etc.)
 - C. Meteorological precipitation of any kind, (e.g. a quarter inch or more rainfall, sleet, snow, and/or freeze thaw conditions) which is sufficient in the amount or condition to achieve control of fugitive emissions from these areas while the plant is operating.
 - D. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads. The operator(s) shall record a brief description of such events in the same log as the documented watering.
 - E. The operator(s) shall record the date and the amount of water applied for each application on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

¹ For purposes of this document, Control of Fugitive Emissions means to control particulate matter that is not collected by a capture system and visible emissions to the extent necessary to prevent violations of the air pollution law or regulation. (Note: control of visible emission is not the only factor to consider in protection of ambient air quality.)

For Vehicle Activity Areas around Open Storage Piles:

1. Pavement of Stockpile Vehicle Activity Surfaces –
 - A. The operator(s) may pave all or any portion of the vehicle activity areas around the storage piles with materials such as asphalt, concrete, and/or other material(s) after receiving approval from the program. The pavement will be applied in accordance with industry standards for such pavement so as to achieve control of fugitive emissions while the plant is operating.
 - B. Maintenance and/or repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall periodically water, wash and/or otherwise clean all of the paved portions of the vehicle activity areas around the storage piles as necessary to achieve control of fugitive emissions from these areas while the plant is operating.

2. Usage of Chemical Dust Suppressants –
 - A. The operator(s) shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to all the vehicle activity areas around the open storage piles. The suppressant will be applied in accordance with the manufacturer's suggested application rate (if available) and re-applied as necessary to achieve control of fugitive emissions from these areas while the plant is operating.
 - B. The quantities of the chemical dust suppressant shall be applied, re-applied and/or maintained sufficient to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator(s) shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

3. Usage of Documented Watering –
 - A. The operator(s) shall control the fugitive emissions from all the vehicle activity areas around the storage piles at the installation by consistently and correctly using the application of a water spray. Documented watering will be applied in accordance with a recommended application rate of 100 gallons per day per 1,000 square feet of unpaved/untreated surface area of vehicle activity areas around the storage piles as necessary to achieve control of fugitive emissions from these areas while the plant is operating. (Refer to example for documented watering of haul roads.)
 - B. The operator(s) shall maintain a log that documents daily water applications. This log shall include, but is not limited to, date and volumes (e.g., number of tanker applications and/or total gallons used) of water application. The log shall also record rationale for not applying water on day(s) the plant is in operations (e.g., meteorological situations, precipitation events, freezing, etc.)
 - C. Meteorological precipitation of any kind, (e.g. a quarter inch or more rainfall, sleet, snow, and/or freeze thaw conditions) which is sufficient in the amount or condition to achieve control of fugitive emissions from these areas while the plant is operating.
 - D. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads. The operator(s) shall record a brief description of such events in the same log as the documented watering.
 - E. The operator(s) shall record the date and the amount of water applied for each application on the above areas. The operator(s) shall keep these records with the plant for not less than five (5) years, and the operator(s) shall make these records available to Department of Natural Resources personnel upon request.

Mr. Wayne Ellett
Assistant Manager
Doss & Harper Stone Co., Inc.
P.O. Box 888
West Plains, MO 65775

RE: New Source Review Permit - Project Number: 2006-09-007

Dear Mr. Ellett:

Enclosed with this letter is your New Source Review permit. Please review your permit carefully and note the special conditions, if any, and the requirements in your permit.

Operation in accordance with the conditions and requirements in your permit and the New Source Review application submitted for project 2006-09-007 is necessary for continued compliance. The section of the permit entitled "Technical Review of Application for Authority to Construct" should not be separated from the main portion of your permit. The entire permit must be retained in your files. The reverse side of your permit certificate has important information concerning standard permit conditions and your rights and obligations under the laws and regulations of the State of Missouri.

If you have any questions, please contact me at (573) 751-4817, or write the Department of Natural Resources' Air Pollution Control Program, PO Box 176, Jefferson City, MO 65102. Thank you for your attention to this matter.

Sincerely,

AIR POLLUTION CONTROL PROGRAM

Kendall B. Hale
New Source Review Unit Chief

KH: sak

Enclosures

c: Southeast Regional Office
PAMS File: 2006-09-007
Permit Number: