

STATE OF MISSOURI
DEPARTMENT OF NATURAL RESOURCES

MISSOURI CLEAN WATER COMMISSION



MISSOURI STATE OPERATING PERMIT

In compliance with the Missouri Clean Water Law, (Chapter 644 R.S. Mo. as amended, hereinafter, the Law), and the Federal Water Pollution Control Act (Public Law 92-500, 92nd Congress) as amended,

Permit No. MO-0123358

Owner: Koller Enterprises
Address: 1400 South Highway 141, Fenton, MO 63026

Continuing Authority: Same as above
Address: Same as above

Facility Name: Koller Craft Plastic Products
Address: 1400 South Highway 141, Fenton, MO 63026

Legal Description: US Survey 3011, T43N, R5E, Jefferson County
UTM Coordinates X= 723177, Y = 4262676

Receiving Stream: Saline Creek (C)
First Classified Stream and ID: Saline Creek (C)(02190)
USGS Basin & Sub-watershed No.: (07140102-080004)

is authorized to discharge from the facility described herein, in accordance with the effluent limitations and monitoring requirements as set forth herein:

FACILITY DESCRIPTION

Outfall #001 - Manufacturing - SIC #3089
Non contact cooling water and storm water runoff.
Maximum flow of cooling water is 0.432 MGD (900 gpm for one eight-hour shift).

This permit authorizes only wastewater discharges under the Missouri Clean Water Law and the National Pollutant Discharge Elimination System; it does not apply to other regulated areas. This permit may be appealed in accordance with Section 644.051.6 of the Law.

May 14, 2010
Effective Date


Mark N. Templeton, Director, Department of Natural Resources

May 13, 2015
Expiration Date


Mike Struckhoff, Director, St. Louis Regional Office

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS					PAGE NUMBER 2 of 7	
					PERMIT NUMBER MO-0123358	
The permittee is authorized to discharge from outfall(s) with serial number(s) as specified in the application for this permit. The final effluent limitations shall become effective upon issuance and remain in effect until expiration of the permit. Such discharges shall be controlled, limited and monitored by the permittee as specified below:						
OUTFALL NUMBER AND EFFLUENT PARAMETER(S)	UNITS	FINAL EFFLUENT LIMITATIONS			MONITORING REQUIREMENTS	
		DAILY MAXIMUM	WEEKLY AVERAGE	MONTHLY AVERAGE	MEASUREMENT FREQUENCY	SAMPLE TYPE
Outfall #001						
Flow	MGD	*		*	once/month	24 hr. estimate
Oil and Grease	mg/L	15		10	once/year**	grab
Chemical Oxygen Demand	mg/L	*		*	once/year**	grab
Chemicals currently stored outside or in the last 3 years (See Sampling Req.)	mg/L	*		*	once/year**	grab
pH – Units	SU	***		***	once/year**	grab
Settleable Solids	mL/L/hr	*		*	once/year**	grab
Color****		*		*	once/year**	grab
<u>Instream Monitoring</u> - 50 feet above Outfall #001						
Temperature	°F	*		*	once/month	grab
<u>Downstream Monitoring</u> - 100 feet below Outfall #001						
Temperature	°F	*****		*****	once/month	grab
MONITORING REPORTS SHALL BE SUBMITTED ANNUALLY ; THE FIRST REPORT IS DUE October 28, 2010 . THERE SHALL BE NO DISCHARGE OF FLOATING SOLIDS OR VISIBLE FOAM IN OTHER THAN TRACE AMOUNTS.						
B. STANDARD CONDITIONS						
IN ADDITION TO SPECIFIED CONDITIONS STATED HEREIN, THIS PERMIT IS SUBJECT TO THE ATTACHED Part I STANDARD CONDITIONS DATED <u>October 1, 1980 and August 15, 1994</u> , AND HEREBY INCORPORATED AS THOUGH FULLY SET FORTH HEREIN.						

MO 780-0010 (8/91)

A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS (continued)

- * Monitoring requirement only.
- ** Permittee shall collect and analyze one sample per year, taken during a rainfall which exceeds 0.1 inches and results in a discharge, and also at any time at the request of the department.
- *** pH is measured in pH units and is not to be averaged. The pH is limited to the range of 6.0-9.0 pH units.
- **** Description of the visual appearance of the effluent. For example: clear, green, black, etc.
- ***** Effluent shall not elevate or depress the temperature of the receiving stream beyond the mixing zone more than five (5°)F. The stream temperature beyond the mixing zone shall not exceed ninety (90°)F due to the effluent.

C. SPECIAL CONDITIONS

1. This permit may be reopened and modified, or alternatively revoked and reissued, to:
 - (a) Comply with any applicable effluent standard or limitation issued or approved under Sections 301(b)(2)(C) and (D), 304(b)(2), and 307(a) (2) of the Clean Water Act, if the effluent standard or limitation so issued or approved:
 - (1) contains different conditions or is otherwise more stringent than any effluent limitation in the permit; or
 - (2) controls any pollutant not limited in the permit.
 - (b) Incorporate new or modified effluent limitations or other conditions, if the result of a waste load allocation study, toxicity test or other information indicates changes are necessary to assure compliance with Missouri's Water Quality Standards.
 - (c) Incorporate new or modified effluent limitations or other conditions if, as the result of a watershed analysis, a Total Maximum Daily Load (TMDL) limitation is developed for the receiving waters which are currently included in Missouri's list of waters of the state not fully achieving the state's water quality standards, also called the 303(d) list.

The permit as modified or reissued under this paragraph shall also contain any other requirements of the Clean Water Act then applicable.

2. All outfalls must be clearly marked in the field.
3. Permittee will cease discharge by connection to a facility with an area-wide management plan per 10 CSR 20-6.010(3)(B) within 90 days of notice of its availability.
4. Changes in Discharges of Toxic Substances

The permittee shall notify the Director as soon as it knows or has reason to believe:

- (a) That any activity has occurred or will occur which would result in the discharge of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "notification levels:"
 - (1) One hundred micrograms per liter (100 µg/L);
 - (2) Two hundred micrograms per liter (200 µg/L) for acrolein and acrylonitrile; five hundred micrograms per liter (500 µg/L) for 2,5 dinitrophenol and for 2-methyl-4, 6-dinitrophenol; and one milligram per liter (1 mg/L) for antimony;
 - (3) Five (5) times the maximum concentration value reported for the pollutant in the permit application;
 - (4) The level established in Part A of the permit by the Director.
 - (b) That they have begun or expect to begin to use or manufacture as an intermediate or final product or byproduct any toxic pollutant, which was not reported in the permit application.
5. Report as no-discharge when a discharge does not occur during the report period.
 6. Water Quality Standards
 - (a) Discharges to waters of the state shall not cause a violation of water quality standards rule under 10 CSR 20-7.031, including both specific and general criteria.
 - (b) General Criteria. The following general water quality criteria shall be applicable to all waters of the state at all times including mixing zones. No water contaminant, by itself or in combination with other substances, shall prevent the waters of the state from meeting the following conditions:
 - (1) Waters shall be free from substances in sufficient amounts to cause the formation of putrescent, unsightly or harmful bottom deposits or prevent full maintenance of beneficial uses;
 - (2) Waters shall be free from oil, scum and floating debris in sufficient amounts to be unsightly or prevent full maintenance of beneficial uses;
 - (3) Waters shall be free from substances in sufficient amounts to cause unsightly color or turbidity, offensive odor or prevent full maintenance of beneficial uses;
 - (4) Waters shall be free from substances or conditions in sufficient amounts to result in toxicity to human, animal or aquatic life;
 - (5) There shall be no significant human health hazard from incidental contact with the water;
 - (6) There shall be no acute toxicity to livestock or wildlife watering;
 - (7) Waters shall be free from physical, chemical or hydrologic changes that would impair the natural biological community;
 - (8) Waters shall be free from used tires, car bodies, appliances, demolition debris, used vehicles or equipment and solid waste as defined in Missouri's Solid Waste Law, section 260.200, RSMo, except as the use of such materials is specifically permitted pursuant to section 260.200-260.247.

C. SPECIAL CONDITIONS (continued)

7. The permittee shall comply with any applicable requirements listed in 10 CSR 20-8 and 10 CSR 20-9, unless the facility has received written notification that the Department has approved a modification to the requirements. The monitoring frequencies contained in this permit shall not be construed by the permittee as a modification of the monitoring frequencies listed in 10 CSR 20-9. If a modification of the monitoring frequencies listed in 10 CSR 20-9 is needed, the permittee shall submit a written request to the department for review and, if deemed necessary, approval.
8. All paint, solvents, petroleum products and petroleum waste products (except fuels), and storage containers (such as drums, cans, or cartons) shall be stored so that these materials are not exposed to storm water. Spill prevention, control, and/or management shall be provided sufficient to prevent any spills of these pollutants from entering a water of the state. Any containment system used to implement this requirement shall be constructed of materials compatible with the substances contained and shall also prevent the contamination of groundwater.
9. Collection facilities shall be provided on-site, and arrangement made for proper disposal of (non-wood) waste products, including but not limited to, petroleum waste products and solvents.
10. Good housekeeping practices shall be maintained on the site to keep solid waste from entering waters of the state.
11. All fueling facilities present on the site shall adhere to applicable federal and state regulations concerning underground storage, above ground storage, and dispensers, including spill prevention, control and counter measures.
12. An individual shall be designated by the permittee as responsible for environmental matters. Staff of the permitted facility shall inspect, on workdays, any structures that function to prevent pollution of storm water or to remove pollutants from storm water and of the facility in general to ensure that any Best Management Practices are continually implemented and effective.
13. Substances regulated by federal law under the Resource Conservation and Recovery Act (RCRA) or the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) that are transported, stored, or used for maintenance, cleaning or repair shall be managed according to the provisions of RCRA and CERCLA.
14. All involved personnel shall be trained in material handling and storage, and housekeeping of maintenance areas. Upon request, proof of training shall be submitted to the Department.

STORMWATER SAMPLING REQUIREMENTS

1. The permittee shall collect and analyze one representative sample per year taken during a rainfall, which exceeds 0.1 inches and results in a discharge. The sample shall be analyzed for chemicals listed in 40 CFR 122 Appendix D (see Attachment 1) which are currently or have been stored outside in the last three years in open or unsecured containers, loaded or unloaded, and exposed to storm water. A secure container shall be deemed to be a container with a lid, which has never been opened since it was originally sealed.
2. Other soluble bulk materials that are not listed in 40CFR 122 Appendix D (see Attachment 1) that are actually stored outside and exposed to storm water must also be monitored. If permittee has questions concerning which parameters to sample and test for, contact the Water Pollution Control Program.
3. Exempted from monitoring requirements are iron and aluminum, when stored outside in the form of solid pieces of steel and aluminum, and gases.

Attachment 1

Appendix D, To Part 122 - NPDES Permit Application Testing Requirements (122.21)

Table II - Organic Toxic Pollutants In Each Of Four Fractions In Analysis By Gas Chromatography/Mass Spectroscopy (GS/MS).

Volatiles

- 1V acrolein
- 2V acrylonitrile
- 3V benzene
- 5V bromoform
- 6V carbon tetrachloride
- 7V chlorobenzene
- 8V chlorodibromomethane
- 9V chloroethane
- 10V 2-chloroethylvinyl ether
- 11V chloroform
- 12V dichlorobromomethane
- 14V 1,1-dichloroethane
- 15V 1,2-dichloroethane
- 16V 1,1-dichloroethylene
- 17V 1,2-dichloropropane
- 18V 1,3-dichloropropylene
- 19V ethylbenzene
- 20V methyl bromide
- 21V methyl chloride
- 22V methylene chloride
- 23V 1,1,2,2-tetrachloroethane
- 24V tetrachloroethylene
- 25V toluene
- 26V 1,2-trans-dichloroethylene
- 27V 1,1,1-trichloroethane
- 28V 1,1,2-trichloroethane
- 29V trichloroethylene
- 31V vinyl chloride

Acid Compounds

- 1A 2-chlorophenol
- 2A 2,4-dichlorophenol
- 3A 2,4-dimethylphenol
- 4A 4,6-dinitro-o-cresol
- 5A 2,4 dinitrophenol
- 6A 2-nitrophenol
- 7A 4-nitrophenol
- 8A p-chloro-m-cresol
- 9A pentachlorophenol
- 10A phenol
- 11A 2,4,6-trichlorophenol

Base/Neutral

- 1B acenaphthene
- 2B acenaphthylene
- 3B anthracene
- 4B benzidine
- 5B benzo(a)anthracene
- 6B benzo(a)pyrene
- 7B 3,4-benzofluoranthene
- 8B benzo(ghi)perylene
- 9B benzo(k)fluoranthene
- 10B bis(2-chloroethoxy)methane
- 11B bis(2-chloroethyl)ether
- 12B bis(2-chloroisopropyl)ether
- 13B bis(2-ethylhexyl)phthalate
- 14B 4-bromophenyl phenyl ether
- 15B butylbenzyl phthalate
- 16B 2-chloronaphthalene
- 17B 4-chlorophenyl phenyl ether
- 18B chrysene
- 19B dibenzo(a,h)anthracene
- 20B 1,2-dichlorobenzene
- 21B 1,3-dichlorobenzene
- 22B 1,4-dichlorobenzene
- 23B 3,3'-dichlorobenzidine
- 24B diethyl phthalate
- 25B dimethyl phthalate
- 26B di-n-butyl phthalate
- 27B 2,4-dinitrotoluene
- 28B 2,6-dinitrotoluene
- 29B di-n-octyl phthalate
- 30B 1,2-diphenylhydrazine (as azobenzene)
- 31B fluoranthene
- 32B fluorene
- 33B hexachlorobenzene
- 34B hexachlorobutadiene
- 35B hexachlorocyclopentadiene
- 36B hexachloroethane
- 37B indeno(1,2,3-cd)pyrene
- 38B isophorone
- 39B naphthalene
- 40B nitrobenzene
- 41B N-nitrosodimethylamine
- 42B N-nitrosodi-n-propylamine
- 43B N-nitrosodiphenylamine
- 44B phenanthrene
- 45B pyrene
- 46B 1,2,4-trichlorobenzene

(continued on next page)

Attachment 1 (continued)

Pesticides

- 1P aldrin
- 2P alpha-BHC
- 3P beta-BHC
- 4P gamma-BHC
- 5P delta-BHC
- 6P chlordane
- 7P 4,4'-DDT
- 8P 4,4'-DDE
- 9P 4,4'-DDD
- 10P dieldrin
- 11P alpha-endosulfan
- 12P beta-endosulfan
- 13P endosulfan sulfate
- 14P endrin
- 15P endrin aldehyde
- 16P heptachlor
- 17P heptachlor epoxide
- 18P PCB-1242
- 19P PCB-1254
- 20P PCB-1221
- 21P PCB-1232
- 22P PCB-1248
- 23P PCB-1260
- 24P PCB-1016
- 25P toxaphene

Table III - Other Toxic
Pollutants (Metals and Cyanide)
and Total Phenols

- Antimony, Total
- Arsenic, Total
- Beryllium, Total
- Cadmium, Total
- Chromium, Total
- Copper, Total
- Lead, Total
- Mercury, Total
- Nickel, Total
- Selenium, Total
- Silver, Total
- Thallium, Total
- Zinc, Total
- Cyanide, Total
- Phenols, Total

Table IV - Conventional and Nonconventional
Pollutants Required to be Tested by Existing
Dischargers if Expected to be Present

- Bromide
- Chlorine, Total Residual
- Color
- Fecal Coliform
- Fluoride
- Nitrate-Nitrite
- Nitrogen, Total Organic
- Oil and Grease
- Phosphorus, Total
- Radioactivity
- Sulfate
- Sulfide
- Sulfite
- Surfactants
- Aluminum, Total
- Barium, Total
- Boron, Total
- Cobalt, Total
- Iron, Total
- Magnesium, Total
- Molybdenum, Total
- Manganese, Total
- Tin, Total
- Titanium, Total

Table V - Toxic Pollutants and
Hazardous Substances Required To Be
Identified by Existing Dischargers
if Expected To Be Present

Toxic Pollutants

Asbestos

Hazardous Substances

- Acetaldehyde
- Allyl alcohol
- Allyl chloride
- Amyl acetate
- Aniline
- Benzonitrile
- Benzyl chloride
- Butyl acetate
- Butylamine
- Captan
- Carbaryl
- Carbofuran

(continued on next page)

Attachment 1
Table V - (continued)

Hazardous Substances (continued)

Carbon disulfide	Pyrethrins
Chlorpyrifos	Quinoline
Coumaphos	Resorcinol
Cresol	Strontium
Crotonaldehyde	Strychnine
Cyclohexane	Styrene
2,4-D(2,4-Dichlorophenoxy acetic acid)	2,4,5-T(2,4,5-Trichlorophenoxy acetic acid)
Diazinon	TDE(Tetrachlorodiphenylethane)
Dicamba	2,4,5-TP [2-(2,4,5-Trichlorophenoxy) propanoic acid]
Dichlobenil	Trichlorofan
Dichlone	Triethanolamine dodecylbenzenesulfonate
2,2-Dichloropropionic acid	Triethylamine
Dichlorvos	Trimethylamine
Diethyl amine	Uranium
Dimethyl amine	Vanadium
Dintrobenzene	Vinyl acetate
Diquat	Xylene
Disulfoton	Xylenol
Diuron	Zirconium
Epichlorohydrin	
Ethion	
Ethylene diamine	
Ethylene dibromide	
Formaldehyde	
Furfural	
Guthion	
Isoprene	
Isopropanolamine Dodecylbenzenesulfonate	
Kelthane	
Kepone	
Malathion	
Mercaptodimethur	
Methoxychlor	
Methyl mercaptan	
Methyl methacrylate	
Methyl parathion	
Mevinphos	
Mexacarbate	
Monoethyl amine	
Monomethyl amine	
Naled	
Napthenic acid	
Nitrotoluene	
Parathion	
Phenolsulfanate	
Phosgene	
Propargite	
Propylene oxide	

Missouri Department of Natural Resources
Statement of Basis
Koller Craft Plastic Products
NPDES #: MO-0123358

A Statement of Basis (Statement) gives pertinent information regarding the applicable regulations and rationale for the development of the NPDES Missouri State Operating Permit (operating permit). Statement of Basis are required for all operating permits for which a Fact Sheet is not required. Statement of Basis briefly describe, among other items, the derivation of the effluent limitation and the reasons for operating permit's Special Conditions. Fact Sheets should be developed for any permit that requires complex calculations or special conditions; and this is particularly true for permit conditions based on Best Professional Judgment (BPJ).

A Statement is not an enforceable part of an operating permit.

Part I – Facility Information

Facility Type: Industrial, non-contact cooling water and storm water
Facility SIC #: 3089

Facility Description:

Non contact cooling water and storm water runoff.
Maximum flow of cooling water is 0.432 MGD (900 gpm for one eight-hour shift).

Receiving Water Body's Water Quality & Facility Performance History:

In the past five years of discharge monitoring reports submitted to the department, this facility has been in compliance with the effluent limitations in the current permit.
Ten years of temperature data has been provided for samples taken 50' above and 100' below the outfall. Since 1999 there have only been 8 incidences where the temperature was elevated or depressed more than 5 degrees Fahrenheit.

Comments:

No comments

Part II – Operator Certification Requirements

As per [10 CSR 20-6.010(8) Terms and Conditions of a Permit], permittees shall operate and maintain facilities to comply with the Missouri Clean Water Law and applicable permit conditions and regulations. Operators or supervisors of operations at regulated wastewater treatment facilities shall be certified in accordance with [10 CSR 20-9.020(2)] and any other applicable state law or regulation. As per [10 CSR 20-9.010(2)(A)], requirements for operation by certified personnel shall apply to all wastewater treatment systems, if applicable, as listed below:

Check boxes below that are applicable to the facility;

- Owned or operated by or for:
 - Municipalities
 - Public Sewer District:
 - County
 - Public Water Supply Districts:
 - Private sewer company regulated by the Public Service Commission:
 - State or Federal agencies:

Each of the above entities are only applicable if they have a Population Equivalent greater than two hundred (200) and/or fifty (50) or more service connections.

Not Applicable ; This facility is not required to have a certified operator.

Part III – Rationale and Derivation of Effluent Limitations & Permit Conditions

ANTI-BACKSLIDING:

A provision in the Federal Regulations [CWA §303(d)(4); CWA §402(c); 40 CFR Part 122.44(I)] that requires a reissued permit to be as stringent as the previous permit with some exceptions.

- All limits in this statement are at least as protective as those previously established; therefore, backsliding does not apply.

AREA-WIDE WASTE TREATMENT MANAGEMENT & CONTINUING AUTHORITY:

As per [10 CSR 20-6.010(3)(B)], ... An applicant may utilize a lower preference continuing authority by submitting, as part of the application, a statement waiving preferential status from each existing higher preference authority, providing the waiver does not conflict with any area-wide management plan approved under section 208 of the Federal Clean Water Act or any other regional sewage service and treatment plan approved for higher preference authority by the department.

COMPLIANCE AND ENFORCEMENT:

Enforcement is the action taken by the Water Protection Program (WPP) to bring an entity into compliance with the Missouri Clean Water Law, its implementing regulations, and/or any terms and conditions of an operating permit. The primary purpose of the enforcement activity in the WPP is to resolve violations and return the entity to compliance.

Not Applicable ;

The permittee/facility is not currently under Water Protection Program enforcement action.

OUTFALL #001: Effluent limitations have been reassessed and verified that they are still protective of the receiving stream's Water Quality. Therefore, effluent limitations have been retained from previous state operating permit – no changes proposed.

REMOVAL EFFICIENCY:

Removal efficiency is a method by which the Federal Regulations define Secondary Treatment and Equivalent to Secondary Treatment, which applies to Biochemical Oxygen Demand 5-day (BOD₅) and Total Suspended Solids (TSS) for Publicly Owned Treatment Works (POTWs)/municipals. Please see the United States Environmental Protection Agency's (EPA) website for interpretation of percent removal requirements for National Pollutant Discharge Elimination System Permit Application Requirements for Publicly Owned Treatment Works and Other Treatment Works Treating Domestic Sewage @ www.epa.gov/fedrgstr/EPA-WATER/1999/August/Day-04/w18866.htm

Not Applicable ;

This wastewater treatment facility is not a POTW. Influent monitoring is not being required to determine percent removal.

Sanitary Sewer Overflows (SSOs), Bypasses, Inflow & Infiltration (I&I) – Prevention/Reduction:

Sanitary Sewer Systems (SSSs) are municipal wastewater collection systems that convey domestic, commercial, and industrial wastewater, and limited amounts of infiltrated groundwater and storm water (i.e. I&I), to a POTW. SSSs are not designed to collect large amounts of storm water runoff from precipitation events.

Untreated or partially treated discharges from SSSs are commonly referred to as SSOs. SSOs have a variety of causes including blockages, line breaks, sewer defects that allow excess storm water and ground water to overload the system, lapses in sewer system operation and maintenance, inadequate sewer design and construction, power failures, and vandalism. A SSO is defined as an untreated or partially treated sewage release from a SSS. SSOs can occur at any point in an SSS, during dry weather or wet weather. SSOs include overflows that reach waters of the state. SSOs also include overflows out of manholes and onto city streets, sidewalks, and other terrestrial locations. SSSs can back up into buildings, including private residences. When sewage backups are caused by problems in the publicly-owned portion of an SSS, they are considered SSOs.

At this time, the department recommends the US EPA's Guide for Evaluating Capacity, Management, Operation and Maintenance (CMOM) Programs At Sanitary Sewer Collection Systems (Document # EPA 305-B-05-002). The CMOM identifies some of the criteria used by the EPA to evaluate a collection system's management, operation, and maintenance and was intended for use by the EPA, state, regulated community, and/or third party entities. The CMOM is applicable to small, medium, and large systems; both public and privately owned; and both regional and satellite collection systems. The CMOM does not substitute for the Clean Water Act, the Missouri Clean Water Law, and both federal and state regulations, as it is not a regulation.

Not Applicable ;

This facility is not required to develop or implement a program for maintenance and repair of the collection system; however, it is a violation of Missouri State Environmental Laws and Regulations to allow untreated wastewater to discharge to waters of the state.

SCHEDULE OF COMPLIANCE (SOC):

A schedule of remedial measures included in a permit, including an enforceable sequence of interim requirements (actions, operations, or milestone events) leading to compliance with the Missouri Clean Water Law, its implementing regulations, and/or the terms and conditions of an operating permit.

Not Applicable ;

This permit does not contain a SOC.

STORM WATER POLLUTION PREVENTION PLAN (SWPPP):

In accordance with 40 CFR 122.44(k) *Best Management Practices (BMPs)* to control or abate the discharge of pollutants when: (1) Authorized under section 304(e) of the Clean Water Act (CWA) for the control of toxic pollutants and hazardous substances from ancillary industrial activities; (2) Authorized under section 402(p) of the CWA for the control of storm water discharges; (3) Numeric effluent limitations are infeasible; or (4) the practices are reasonably necessary to achieve effluent limitations and standards or to carry out the purposes and intent of the CWA.

In accordance with the EPA's *Storm Water Management for Industrial Activities: Developing Pollution Prevention Plans and Best Management Practices* [EPA 832-R-92-006] (Storm Water Management), BMPs are measures or practices used to reduce the amount of pollution entering (regarding this operating permit) waters of the state. BMPs may take the form of a process, activity, or physical structure.

Additionally in accordance with the Storm Water Management, a SWPPP is a series of steps and activities to (1) identify sources of pollution or contamination, and (2) select and carry out actions which prevent or control the pollution of storm water discharges.

Not Applicable ;

At this time, the permittee is not required to develop and implement a SWPPP.

WATER QUALITY STANDARDS:

Per [10 CSR 20-7.031(3)], General Criteria shall be applicable to all waters of the state at all times including mixing zones.

Additionally, [40 CFR 122.44(d)(1)] directs the department to establish in each NPDES permit to include conditions to achieve water quality established under Section 303 of the Clean Water Act, including State narrative criteria for water quality.

WHOLE EFFLUENT TOXICITY (WET) TEST:

A WET test is a quantifiable method of determining if a discharge from a facility may be causing toxicity to aquatic life by itself, in combination with or through synergistic responses when mixed with receiving stream water.

Not Applicable ;

At this time, the permittee is not required to conduct WET test for this facility.

303(d) LIST & TOTAL MAXIMUM DAILY LOAD (TMDL):

Section 303(d) of the federal Clean Water Act requires that each state identify waters that are not meeting water quality standards and for which adequate water pollution controls have not been required. Water quality standards protect such beneficial uses of water as whole body contact (such as swimming), maintaining fish and other aquatic life, and providing drinking water for people, livestock and wildlife. The 303(d) list helps state and federal agencies keep track of waters that are impaired but not addressed by normal water pollution control programs.

A TMDL is a calculation of the maximum amount of a given pollutant that a body of water can absorb before its water quality is affected. If a water body is determined to be impaired as listed on the 303(d) list, then a watershed management plan will be developed that shall include the TMDL calculation

Not Applicable ;

This facility does not discharge to a 303(d) listed stream.

Part IV – Administrative Requirements

On the basis of preliminary staff review and the application of applicable standards and regulations, the Department, as administrative agent for the Missouri Clean Water Commission, proposes to issue a permit(s) subject to certain effluent limitations, schedules, and special conditions contained herein and within the operating permit. The proposed determinations are tentative pending public comment.

Date of Statement of Basis: March 11, 2010

Tracy A. Haag
Environmental Engineer
St. Louis Regional Office
7545 S. Lindbergh, Suite 210
St. Louis, MO 63125
(314) 416-2960
tracy.haag@dnr.mo.gov