G01608

OGC# 20001

Schlumberger INDUCTION-ELECTRICAL LOG

COMPANY: LONE STAR PRODUCING CO

WELL: ANDERSON #1

FIELD: WILDCAT

COUNTY: NODAWAY STATE: MISSOURI

LOCATION: 330' WL 2310' NL

Other Services: CNL-FDC-GR

Sec. 17 Twp. 65N Rge. 37W

Permanent Datum: GROUND, Elev. 911

Log Measured From: KB, 4 Ft. Above Perm. Datum

Drilling Measured From: KB

Elev.: K.B. 915; D.F. —; G.L. 911

COUNTY / FIELD or LOCATION / WELL / COMPANY

Date	7-13-73	TOPS MARKED ON		
Run No.	ONE			
Depth—Driller	2273	5 INCH		
Depth—Logger	2244			
Btm. Log Interval	2238			
Top Log Interval	330			
Casing—Driller	8 5/8 @ 350	@	@	@
Casing—Logger	330			
Bit Size	7 7/8			
Type Fluid in Hole	FSH WTR			
Dens. / Visc.	NC / NC			
pH / Fluid Loss	NC / NC ml	ml	ml	ml
Source of Sample	PIT			
R_m @ Meas. Temp.	2.8 @ 78 °F	@ °F	@ °F	@ °F
R_{mf} @ Meas. Temp.	— @ — °F	@ °F	@ °F	@ °F
R_{mc} @ Meas. Temp.	— @ — °F	@ °F	@ °F	@ °F
Source: R_{mf} / R_{mc}	— / —			
R_m @ BHT	@ °F	@ °F	@ °F	@ °F
Time Since Circ.	2 hrs			
Max. Rec. Temp.	97 °F	°F	°F	°F
Equip. / Location	4571 / WICHITA			
Recorded By	McGuiness			
Witnessed By	—			

FOLD HERE The well name, location and borehole reference data were furnished by the customer.

REMARKS: SO # 83759

Changes in Mud Type or Additional Samples				
Date / Sample No.				
Depth—Driller				
Type Fluid in Hole				
Dens. / Visc.				
ph / Fluid Loss		ml		ml
Source of Sample				
R_m @ Meas. Temp.	@	°F	@	°F
R_{mf} @ Meas. Temp.	@	°F	@	°F
R_{mc} @ Meas. Temp.	@	°F	@	°F
Source: R_{mf} / R_{mc}				
R_m @ BHT	@	°F	@	°F
R_{mf} @ BHT	@	°F	@	°F
R_{mc} @ BHT	@	°F	@	°F

Scale Changes			
Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data			
Run No.	Tool Type	Tool Position	Other

Run No.: ONE
C.D.: USED
S.O.: 15"
Equip. PANEL No.: DIP-CB-204
Used: CART. No.: DIC-B-154
SONDE No.: DIS-DB-48
IAP No.: MMP-B-118
S.B.R.: 2
GR CART. No.: —
T.C.: —
F.P.M.: —

Check one, filling in blanks where applicable:
[X] Surface determined sonde errors used for 6FF40.
[ ] 6FF40 sonde error corrected for ___ inch borehole signal at Rm = ___
[ ] 6FF40 zero set in hole at depth of ___ feet.

SPONTANEOUS-POTENTIAL millivolts	DEPTHS	CONDUCTIVITY millimhos/m = $\frac{1000}{ohms.\ m^2/m}$
— 20 +		6FF40 INDUCTION: 1000 — 500 — 0
		RESISTIVITY -ohms. m²/m
		LATEROLOG 8 AVERAGED: 0 — 50; 0 — 500
		DEEP INDUCTION: 0 — 50; 0 — 500