SCHLUMBERGER

SCHLUMBERGER WELL SURVEYING CORPORATION
HOUSTON, TEXAS

INDUCTION LOG

COUNTY PIKE	
FIELD or LOCATION WILDCAT SEC. 9-52N-2W	
WELL RAYMOND F. ORF #1	
COMPANY B. F. & S. OIL CO., INC.	
COMPANY B. F. & S. OIL COMPANY, INC.	
WELL RAYMOND F. ORF #1	
FIELD WILDCAT	
LOCATION SEC. 9-52N-2W	
COUNTY PIKE	
STATE MISSOURI	
FILING No.	
Elevation K.B.: N/A D.F.: N/A G.L.: N/A	
Location of Well 990' S. & 2011' W. of SE/CORNER	
OTHER SERVICES GRN	

Run No.	ONE	TWO	
Date	12-7-63		
Depth Driller	97		
Depth Logger	97		
Bottom Log Interval	97		
Top Log Interval	SURF.		
Casing Driller	8 5/8" @ 20'		
Casing Logger	20'		
Bit Size	7 7/8"		
Type Fluid in Hole	CLEAN WATER		
Dens.			
Visc.			
pH			
Fluid Loss			
Source of Sample			
R_m @ Meas. Temp.	@ °F	@ °F	
R_{mf} @ Meas. Temp.	@ °F	@ °F	
R_{mc} @ Meas. Temp.	@ °F	@ °F	
Source: R_{mf} R_{mc}			
R_m @ BHT	@ °F	@ °F	
R_{mf} @ BHT	@ °F	@ °F	
R_{mc} @ BHT	@ °F	@ °F	
Max. Rec. Temp.	61		
Equipment Location	CC 30 mi		
Recorded by	WM. LOW		
Witnessed by	MR. LINCOLN		

REMARKS

FOLD HERE

REMARKS

Changes in Mud Type or Additional Samples			Scale Changes			
Date	Sample No.		Type Log	Depth	Scale Up Hole	Scale Down Hole
Depth—Driller						
Type Fluid in Hole						
Dens.	Visc.					
pH	Fluid Loss	ml				
Source of Sample			Equipment Data			
R_m @ Meas. Temp.	@ °F	@ °F	Run No.	Tool Type	Tool Position	Other
R_{mf} @ Meas. Temp.	@ °F	@ °F				
R_{mc} @ Meas. Temp.	@ °F	@ °F				
Source: R_{mf} R_{mc}						
R_m @ BHT	@ °F	@ °F				
R_{mf} @ BHT	@ °F	@ °F				
R_{mc} @ BHT	@ °F	@ °F				

C.D.: NONE S.O.: 0

Equip. Used: CART. No. IRC-F-135
PANEL No. IRF-F-200 SBR-4
SONDE No. IRC-F-200
IAF-2-105

DEPTHS

CONDUCTIVITY millimhos/m = 1000 / ohms. m²/m

0 — FF40
INDUCTION
200 100 0

RESISTIVITY -ohms. m²/m

A-16"-M
SHORT NORMAL

INDUCTION
0 100
0 1000

0100

0200

INDUCTION
0 100
0 1000

RESISTIVITY -ohms. m²/m

INDUCTION
200 100 0

DEPTHS

CONDUCTIVITY millimhos/m = 1000 / ohms. m²/m

COMPANY B. F. & S. OIL CO., INC.
WELL RAYMOND F. ORF #1
FIELD WILDCAT
COUNTY PIKE STATE MISSOURI

SWSC FR 248
SWSC TD 255
DRLR TD 256
Elev:
KB N/A
DF N/A
GL N/A

DETAIL LOG

5" — 100'

DEPTHS

CONDUCTIVITY millimhos/m = 1000 / ohms. m²/m

INDUCTION
200 100 0

RESISTIVITY -ohms. m²/m

16" NORMAL

INDUCTION
0 100
0 1000

0100

0200

INDUCTION
0 100
0 1000

RESISTIVITY -ohms. m²/m

INDUCTION
200 100 0

DEPTHS

CONDUCTIVITY millimhos/m = 1000 / ohms. m²/m

COMPANY B. F. & S. OIL CO., INC.
WELL RAYMOND F. ORF #1
FIELD WILDCAT
COUNTY PIKE STATE MISSOURI

SWSC FR 248
SWSC TD 255
DRLR TD 256
Elev:
KB N/A
DF N/A
GL N/A