WESTERN WIRELINE LOGING, INC.

00041

Amax Oil
CF-116

6022 10

duplicate

Date JUNE 7, 1976

HOLE NUMBER: CF-116	GAMMA — DENSITY				ELECTRIC		
Well Name					Logged Depth (ft.)	189	189
Elevation	Logged Depth (ft.)	190			Resist. Scale	20	
Depth Drilled	Range				S. P. Scale		20
Log Measured From: Ground Level	Time Constant (sec.)				Logging Speed	20	20
State-County: Wyo. Fremont	Logging Speed				Viscosity · Density		
Region	Paper Speed				Rm = °F		
Project	Probe Number				Rmf = °F		
Location: SW SE SW SE SE	Probe Dia. (in.)				Rmc = °F		
Sec. 34 Twp. 44 N Rng. 18 W	Crystal Size (in.)				SPECIAL RUN		
CLIENT: AMAX Coal	Digital Readout (ft.)				Logged Depth (ft.) 40	Survey:	
Owner: Meadow Lark Farms	Time Base (sec.)				Scale 180-190	210-240	
Drilling Co. Teton	Dead Time (μ sec.)				Paper Speed 5		
Engineer Steve Roth	Digital Dead Time (μ sec.)				Logging Speed 25		
Unit Operator: G. Reynolds	Water Factor ( ) in. Hole						
Unit Number: L-6	Casing Factor ( ) in. Steel						
Job Number: 035.02	K—Factor (x 10 ⁻⁶)				CASING — HOLE DATA		
REMARKS:	Calibration				Bit Size 9 7/8 in. to 300 ft.		
	Standard (cps)				Bit Size in. to ft.		
	Bkgnd. Count (cps)				Cased From to ft.		
					Dia. (inside): in., wall size in.		
					Cased From to ft.		
					Dia. (inside): in., wall size in.		