SCHLUMBERGER WELL SURVEYING CORPORATION
HOUSTON, TEXAS

Electrical Log

1199

FIELD PRINT

COMPANY	SHELL OIL CO.
WELL	TEST HOLE (KEEFAUVER) No. 131-C
FIELD	W.C.
COUNTY	VERNON
STATE	MISSOURI
LOCATION	2610'S & 1060'W of NEC
Sec.	7
Twp.	35N
Rge.	33W
Other Services:	—
Permanent Datum:	GL
Elev.	886
Log Measured From	GL, ___ Ft. Above Perm. Datum
Drilling Measured From	GL
Elev.: K.B.	—
D.F.	—
G.L.	886

Date	8-5-63			
Run No.	ONE			
Depth—Driller	388			
Depth—Logger	388			
Btm. Log Interval	387			
Top Log Interval	20			
Casing—Driller	— @ —	@	@	@
Casing—Logger				
Bit Size	4 3/4 (0-24'); 4 1/2 (24'-72')			
Type Fluid in Hole	NATIVE			
Dens. | Visc.	— | —			
pH | Fluid Loss	— | — ml	ml	ml	ml
Source of Sample	FLOW LINE			
R_m @ Meas. Temp.	SEE @ °F	@ °F	@ °F	@ °F
R_{mf} @ Meas. Temp.	REMARKS @ °F	@ °F	@ °F	@ °F
R_{mc} @ Meas. Temp.	@ °F	@ °F	@ °F	@ °F
Source: R_{mf} | R_{mc}				
R_m @ BHT	@ °F	@ °F	@ °F	@ °F
Time Since Circ.	30 MIN			
Max. Rec. Temp.	°F	°F	°F	°F
Equip. | Location	SHA | SHA			
Recorded By	STALL			
Witnessed By	BRUNER			

FOLD HERE — THIS HEADING AND LOG CONFORMS TO API RP 31

REMARKS

Changes in Mud Type or Additional Samples		
Date | Sample No.		
Depth—Driller		
Type Fluid in Hole		
Dens. | Visc.		
ph | Fluid Loss	ml	ml
Source of Sample		
R_m @ Meas. Temp.	@ °F	@ °F
R_{mf} @ Meas. Temp.	@ °F	@ °F
R_{mc} @ Meas. Temp.	@ °F	@ °F
Source: R_{mf} | R_{mc}		
R_m @ BHT	@ °F	@ °F
R_{mf} @ BHT	@ °F	@ °F
R_{mc} @ BHT	@ °F	@ °F

Scale Changes			
Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data				
Run No.	Tool Type	Pad Type	Tool Pos.	Other

	PM MEAS. TEMP.	PM BHT	TM MEAS. TEMP	TM BHT
Rm	6.0 @ 93	8.33 @ 67	6.02 @ 93	8.35 @ 67
Rmf	5.24 @ 93	7.27 @ 67	5.33 @ 93	7.4 @ 67
Rmc	10.21 @ 93	14.2 @ 67	10.3 @ 93	14.3 @ 67

SPONTANEOUS POTENTIAL millivolts	Depths	RESISTIVITY ohms. m²/m	RESISTIVITY ohms. m²/m
10 MV (− +)		SHORT NORMAL: 0–50; 0–500. 18'8" LATERAL: 0–50; 0–500. AMP SHORT NORMAL	LONG NORMAL: 0–50; 0–500