SCHLUMBERGER WELL SURVEYING CORPORATION

SCHLUMBERGER

COMPANY Shell Oil Co.

WELL 1A-5-5-3

FIELD Vernon Area

COUNTY Vernon PARISH STATE La.

Other Services: Induction Laterlog

Sec. 5 Twp. 3S-N Rge. 3S-W No. 73

Permanent Datum: Ground Elev. 801 Elev. K.B. 01801

Log Measured from: Ground Above Perm. Datum

Drilling Measured from: K.B.

COUNTY Phil Rogers
FIELD or LOCATION
WELL

September 20, 1962

Run No.	1		
Date	9-20-62		
Depth-Driller	296		
Depth-Logger	296		
Bottom Log Interval	296		
Top Log Interval	30		
Casing-Driller	8 5/8" @ 30		
Casing-Logger	30		
Bit Size	7 7/8"		
Type Fluid in Hole	Water		
Dens. / Visc.	8.8 / 28		
pH / Fluid Loss	8.5 / 8.4		
Source of Sample	Pit		
R_m @ Meas. Temp	.44 @ 74°F		
R_{mf} @ Meas. Temp	.34 @ 74°F		
R_{mc} @ Meas. Temp	.44 @ 74°F		
Source: R_{mf} / R_{mc}	Pit / Pit		
R_m @ BHT	.19 @ 100°F		
R_{mf} @ BHT	.14 @ 100°F		
R_{mc} @ BHT	.19 @ 100°F		
Time Since Circ.	10 min		
Max. Rec. Temp.	100°F		
Equipment Number	4-5-5		
Location	Vernon		
Recorded By	Hill		
Witnessed By	Mr. Rogers		

REMARKS

Changes in Mud Type or Additional Samples

Date	Sample No.	Depth—Driller	Type Fluid in Hole	Dens.	Visc.	pH	Fluid Loss

Scale Changes

Type Log	Depth	Scale Up Hole	Scale Down Hole

Equipment Data

Run No.	Tool Type	Pad Type	Tool Pos.
One	Dual Mex sonde		

Other: "B" at surface

SPONTANEOUS POTENTIAL millivolts

RESISTIVITY ohms. m²/m — SHORT NORMAL 16" SHORT NORMAL: 0–50; 0–500

18'8" LATERAL 18'8" LATERAL: 0–50; 0–500

RESISTIVITY ohms. m²/m — LONG NORMAL 64" LONG NORMAL: 0–50; 0–500

Depth

10

4710

A"

A'

A'

A"

4-505

TD 296