SUPERIOR WELL SERVICES

SUPERIOR
Phone: 785-625-5594
Fax: 785-625-5620
Colby, Kansas 67701

Company	RUNNING FOXES PETROLEUM, LLC
Well	MEEK # 7A-6
Field	BUCHANAN-WORDEN
County	VERNON
State	MISSOURI

Company: RUNNING FOXES PETROLEUM, LLC
Well: MEEK # 7A-6
Field: BUCHANAN-WORDEN
County: VERNON
State: MISSOURI

Location: SEC. 6 TWP. 30N RGE. 33W
1312 N. & 2,640' FEL
API # NA
Elevation: GL 0 KB 0 DF 0 GRID 0
Other Services: DIL/SDL/CNL/GR/CAL

DUAL INDUCTION SFL/GR LOG

Casing Driller Size at Depth: 7 5/8" @ 20.00 (ft)
Bit Size: 6 3/4"
Type Fluid in Hole: WATER
Density: 8.4
Viscosity: 28
Ph: 7
Fluid Loss: NA
Source of Sample: FLOWLINE
Rm @ Meas. Temp: .159 @ 71
Rmf @ Meas. Temp: .159 @ 71
Rmc @ Meas. Temp: .159 @ 71
Source: Rmf Rmc: MEASURED
Rm @ BHT: .159 @ 71
Time Since Circulation Stopped: 7.5
Time Logger on Bottom: 21:00
Max. Recorded Temperature: 71
Equipment Number: 10-1
Location: HOBART, OK
Recorded By: MR. BRATTON
Witnessed By: MR. CARTER

Equipment Location
Casing Measured From: GL
Drilling Measured From: GL

Permanent Datum	GL	Elevation	0
Log Measured From	GL	Above Permanent Datum	0
Drilling Measured From	GL		

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

CREW: CARTER, BROWN
182-11576 RUNNING
THANK YOU!
PERMIT # 22026

SUPERIOR WELL SERVICES

2" DIL SECTION

Database File: 182-11576 running foxes.db
Dataset Pathname: DIL/pass3.4
Presentation Format: dilcom
Dataset Creation: Fri Dec 14 00:37:50 2007 by Calc Open-Cased-060327
Charted by: Depth in Feet scaled 1:600

Gamma Ray (GAPI) 0 150
Surface Casing
RILD (Ohm-m) 0 50
RILS (Ohm-m) 0 50
RILD (Ohm-m) 50 1000
CALI (mmmm-in) 1000 0
RILD (Ohm-m) 50
RILS (Ohm-m) 50
RILD (Ohm-m) 50 1000

SUPERIOR WELL SERVICES

5" DIL SECTION

Database File: 182-11576 running foxes.db
Dataset Pathname: DIL/pass3.5
Presentation Format: dilfer
Dataset Creation: Fri Dec 14 00:37:54 2007 by Calc Open-Cased-060327
Charted by: Depth in Feet scaled 1:240

Linear (ft) 0 400
LINE TENSION (lbs) 10000 0
Surface Casing
First Reading
Gamma Ray (GAPI) 0 150
LINE TENSION (lbs) 10000 0
Deep Resistivity (Ohm-m) 0.2 2000
Shallow Resistivity (Ohm-m) 0.2 2000
Medium Resistivity (Ohm-m) 0.2 2000

Section	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
CLL3	14.33					
			DIL-LA-DIV (1513)	17.67	3.50	250.00
CALD	6.50					
CALM	3.33					
SP	0.42					

Dataset: 182-11576 running foxes.db: field=well/DIL/pass3.5
Total Length: 17.67 ft
Total Weight: 250.00 lb
O.D.: 3.50 in