Company:	RUNNING FOXES PETROLEUM, LLC
Well:	STONER # 10-C-6
Field:	BUCHANAN-WORDEN
County:	VERNON
State:	MISSOURI

SUPERIOR WELL SERVICES

Company: RUNNING FOXES PETROLEUM, LLC
Well: STONER # 10-C-6
Field: BUCHANAN-WORDEN
County: VERNON State: MISSOURI
Location: API #: NA
SEC. 6 TWP. 36N RGE. 33W
Permanent Datum: GL Elevation: MSL
Log Measured From: GL 1.0 Above Permanent Datum
Drilling Measured From: GL Elevation: KB: 1.0 DF: MSL GL: MSL
Date: 11-Feb-2007
Run Number: ONE
Depth Logged: 214
Depth Logged Interval: 214
Top Log Interval: SURFACE
Bottom Log Interval: 214
Casing Logged: 7 5/8" @ 21'
Type Fluid in Hole: WATER
Max Rec. Temp.: 74 DEGF
Equipment: 5700
Recorded By: D. HAGEN
Witnessed By: MR. BRAYTON

Other Services: LEON

RECEIVED FEB 22 2007 Mo Oil & Gas Council

DUAL INDUCTION SFL/GR LOG

All interpretations are opinions based on inferences from electrical or other measurements, and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

CREW: DONNIE CARTER
192-11564 RUNNING
THANK YOU!
PERMIT # 22028

SUPERIOR WELL SERVICES

2" DIL SECTION

Database File: 192-11564 running foxes.db
Dataset Pathname: Dil/pass3.2
Presentation Format: .dilcfm
Dataset Creation: Fri Feb 16 11:38:46 2007 by Calib Open Cased 060307
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GAPI) 0–150; RILD (Ohm-m) 0.2–20; RILS (Ohm-m) 0.2–20; CILD (mmho-m) 1000–0

Surface Casing

5" DIL SECTION

Database File: 192-11564 running foxes.db
Dataset Pathname: Dil/pass3.4
Presentation Format: .dilcfm
Dataset Creation: Fri Feb 16 11:38:52 2007 by Calib Open Cased 060307
Charted by: Depth in Feet scaled 1:240

Gamma Ray (GAPI) 0–150; LINE TENSION (lbs) 10000–0; Deep Resistivity (Ohm-m) 0.2–2000; Shallow Resistivity (Ohm-m) 0.2–2000; Medium Resistivity (Ohm-m) 0.2–2000

Surface Casing; First Reading

Series	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
DILR	14.33					
			DIL-GAREN (1513)	17.67	3.50	210.00
DILD	4.50					
DILM	9.33					
HR	0.33					

Dataset: 192-11564 running foxes.db/field.well/Dil/pass3.4
Total Length: 17.67 ft
Total Weight: 210.00 lb
O.D: 3.50 in