Schlumberger

Geoquest

COMPENSATED DENSITY LOG
R.JOHNSON # 2

Company: [redacted]
Well: R.JOHNSON # 2
Field: WILDCAT
County: Stanton
State: Kansas
Other Services: DIL, SDL, DSN, BHC, CBL
Permanent Datum: GL
Log Measured From: KB 11 Ft. Above Perm. Datum
Drilling Measured From: KB
Elevation: KB 3350 Ft. GL 3339 Ft.
Date: 03/01/08
Run Number: ONE
Depth Driller: 5300
Depth Logger: 5300
Bottom Logged Interval: 5300
Top Logged Interval: 2100
Casing Driller: 8 5/8 @ 1800
Casing Logger: 1800
Bit Size: 7 7/8
Type Fluid in Hole: CHEMICAL
Density: 9.2
Viscosity: 50
Fluid Loss: 6.4
Source of Sample: FLOWLINE
Rm @ Meas. Temp: .64 @ 75
Rmf @ Meas. Temp: .48 @ 75
Rmc @ Meas. Temp: .86 @ 75
Source of Rmf & Rmc: MEASURED
Rm @ BHT: .32 @ 120
Time Since Circulation: 6 HRS
Time Logged: 03/01/08
Max. Rec. Temp.: 120
Equipment Number: 10-3
Location: 5 MILES SOUTH OF ELKHART
Recorded By: R. ALLEN
Witnessed By: MR. BRAD HERMAN

5 INCH LOG, POROSITIES R.JOHNSON # 2 03/01/08

LOG PARAMETERS

ENTRA DENSITY: 2.65	NEUTRON MATRIX: SANDSTONE	ENTRA DELTA-T: 54	
MAGNETO DISC.: 0	FLUID CUTOFF: .250	RT MUD: 0.64	
PRESENTATION NAME/SCALE: 1 - DEFAULT PORO 5	MEASURED DIS CSL 5	DENSITY: 1 CHAN	

CALIPER, GR, RXO, DENSITY, POROSITY, FEET

5 INCH LOG, POROSITIES R.JOHNSON # 2 03/01/08

LOG PARAMETERS

ENTRA DENSITY: 2.65	NEUTRON MATRIX: SANDSTONE	ENTRA DELTA-T: 54	
MAGNETO DISC.: 0	FLUID CUTOFF: .250	RT MUD: 0.64	
PRESENTATION NAME/SCALE: 1 - DEFAULT PORO 5	MEASURED DIS CSL 5	DENSITY: 1 CHAN	

CALIPER, RXO, GR, DENSITY, POROSITY, FEET

5 INCH LOG, DENSITY R.JOHNSON # 2 03/01/08

LOG PARAMETERS

ENTRA DENSITY: 2.65	NEUTRON MATRIX: SANDSTONE	ENTRA DELTA-T: 54	
MAGNETO DISC.: 0	FLUID CUTOFF: .250	RT MUD: 0.64	
PRESENTATION NAME/SCALE: 1 - DEFAULT DS CSL 5	MEASURED DIS CSL 5	DENSITY: 1 CHAN	

CALIPER, RXO, GR, DENSITY, POROSITY, FEET

5 INCH LOG, DENSITY R.JOHNSON # 2 03/01/08

LOG PARAMETERS

ENTRA DENSITY: 2.65	NEUTRON MATRIX: SANDSTONE	ENTRA DELTA-T: 54	
MAGNETO DISC.: 0	FLUID CUTOFF: .250	RT MUD: 0.64	
PRESENTATION NAME/SCALE: 1 - DEFAULT DS CSL 5	MEASURED DIS CSL 5	DENSITY: 1 CHAN	

CALIPER, RXO, GR, DENSITY, POROSITY, FEET

25 INCH LOG, HIGH RES. DENSITY R.JOHNSON # 2 03/01/08

LOG PARAMETERS

ENTRA DENSITY: 2.65	NEUTRON MATRIX: SANDSTONE	ENTRA DELTA-T: 54	
MAGNETO DISC.: 0	FLUID CUTOFF: .250	RT MUD: 0.64	
PRESENTATION NAME/SCALE: 1 - DEFAULT DS CSL 25	MEASURED DIS CSL 5	DENSITY: 1 CHAN	

CALIPER, RXO, GR, DENSITY, POROSITY, FEET

25 INCH LOG, HIGH RES. DENSITY R.JOHNSON # 2 03/01/08

LOG PARAMETERS

ENTRA DENSITY: 2.65	NEUTRON MATRIX: SANDSTONE	ENTRA DELTA-T: 54	
MAGNETO DISC.: 0	FLUID CUTOFF: .250	RT MUD: 0.64	
PRESENTATION NAME/SCALE: 1 - DEFAULT DS CSL 25	MEASURED DIS CSL 5	DENSITY: 1 CHAN	

CALIPER, RXO, GR, DENSITY, POROSITY, FEET