Gamma
Ray Neutron
Density
Caliper
Resistivity
Induction
Spontaneous Potential
Temperature
Cement Bond
Variable Density
Acoustic Velocity
Dipmeter
Fracture Finder
Borehole Televiewer
Cement Volume
Formation Density
Compensated
Neutron
Laterolog
Micro-Laterolog
Proximity
Microlog
Caliper
Dual Induction
Focused Log
Sonic
Digitized Sonic
Waveform
Cyberdip
Borehole Profile
High Resolution
Dipmeter
Shallow Focused
Electrode
Spherically Focused
Resistivity
Dual Laterolog
Phasor Induction
SFL
Linear Correlation
Nuclear
Caliper
Log
Cement Evaluation
Cement Bond
Log
Segmented Bond
Log
Borehole Compensated
Sonic Array
Acoustic Televiewer
Stress Analysis
Spectral Density
Dual Spaced
Neutron
Litho-Density
Photoelectric
Factor
Litho-Density
Minerals
Analysis
Elemental
Capture
Spectroscopy
Pulsed
Neutron
Capture
Thermal
Neutron
Decay
Time
Reservoir
Saturation
Tool
Gas
Detection
Log
Fluid
Density
Log
Spinner
Flowmeter
Production
Profile
Flowmeter
Hydro-
static
Flowmeter
Temperature
Gradient
Flowmeter
Oxygen
Activation
Water
Flow
Log
Casing
Collar
Locator
Casing
Inspection
Log
Casing
Corrosion
Log
Casing
Thickness
Pipe
Analysis
Log
Formation
Tester
Pressure
Gauge
Downhole
Fluid
Analysis
Coring
Sidewall
Coring
Vertilog

GEOPHYSICAL STUDIES, INC.
P.O. BOX 1369
GRAND JUNCTION, COLORADO 81502
PHONE 242-7769

5 INCH LOG, POROSITIES D.CARSTON # 5 05/22/08

LOG PARAMETERS

ENTRY DENSITY: 2.65 NEUTRON MATRIX: SANDSTONE ENTRY DELTA T: 54
MATRIX DELTA T: 0 FLUID CLUTOFF: 2000 BIT SIZE: 7 7/8
FREQUENCY FOR CORRELATION: 1 PT AVERAGEFT DELTA T: SECTION GRAPH: 1 CYCLE

CALIPER 6 — 16 | DT(SEC) 140 — 40 | POROSITY(%) 40 — -10 | FEET

5 INCH LOG, POROSITIES D.CARSTON # 5 05/22/08

LOG PARAMETERS

ENTRY DENSITY: 2.65 NEUTRON MATRIX: SANDSTONE ENTRY DELTA T: 54
MATRIX DELTA T: 0 FLUID CLUTOFF: 2000 BIT SIZE: 7 7/8
FREQUENCY FOR CORRELATION: 1 PT AVERAGEFT DELTA T: SECTION GRAPH: 1 CYCLE

5 INCH LOG, DENSITY D.CARSTON # 5 05/22/08

LOG PARAMETERS

ENTRY DENSITY: 2.65 NEUTRON MATRIX: SANDSTONE ENTRY DELTA T: 54
MATRIX DELTA T: 0 FLUID CLUTOFF: 2000 BIT SIZE: 7 7/8
FREQUENCY FOR CORRELATION: 1 PT AVERAGEFT DELTA T: SECTION GRAPH: 1 CYCLE

CALIPER 6 — 16 | DT(SEC) 140 — 40 | POROSITY(%) 40 — -10 | FEET

5 INCH LOG, DENSITY D.CARSTON # 5 05/22/08

LOG PARAMETERS

ENTRY DENSITY: 2.65 NEUTRON MATRIX: SANDSTONE ENTRY DELTA T: 54
MATRIX DELTA T: 0 FLUID CLUTOFF: 2000 BIT SIZE: 7 7/8
FREQUENCY FOR CORRELATION: 1 PT AVERAGEFT DELTA T: SECTION GRAPH: 1 CYCLE

CALIPER 6 — 16 | DT(SEC) 140 — 40 | POROSITY(%) 40 — -10 | FEET

25 INCH LOG, HIGH RES. DENSITY D.CARSTON # 5 05/22/08

LOG PARAMETERS

ENTRY DENSITY: 2.65 NEUTRON MATRIX: SANDSTONE ENTRY DELTA T: 54
MATRIX DELTA T: 0 FLUID CLUTOFF: 2000 BIT SIZE: 7 7/8
FREQUENCY FOR CORRELATION: 1 PT AVERAGEFT DELTA T: SECTION GRAPH: 1 CYCLE

FEET | CORP 0.00 — 0.50 | POROSITY(%) 40 — -10 | PERMEAB(MD) 1000 — 0.1 | CALIPER(IN) 6 — 16 | GAMMA 0 — 100 | DT(SEC) 140 — 40

25 INCH LOG, HIGH RES. DENSITY D.CARSTON # 5 05/22/08

LOG PARAMETERS

ENTRY DENSITY: 2.65 NEUTRON MATRIX: SANDSTONE ENTRY DELTA T: 54
MATRIX DELTA T: 0 FLUID CLUTOFF: 2000 BIT SIZE: 7 7/8
FREQUENCY FOR CORRELATION: 1 PT AVERAGEFT DELTA T: SECTION GRAPH: 1 CYCLE

BIT SIZE 7 7/8 | DT(SEC) 140 — 40 | GAMMA 0 — 100 | CALIPER(IN) 6 — 16 | POROSITY(%) 40 — -10 | PERMEAB(MD) 1000 — 0.1 | CORP 0.00 — 0.50 | FEET