Company	Schlumberger
Well	Kaiser-Francis Oil Co.
Field	Wildcat
County	Grant
State	Oklahoma
Other Services	DIL, BHC, CDL, CNL, HRD
Permanent Datum	Ground Level
Elevation	3600 ft
Log Measured From	Kelly Bushing
Drilling Measured From	Kelly Bushing
Elevation	K.B. 3614 ft
D.F. 3613 ft	G.L. 3600 ft
Date	1-Jan-1900
Run Number	ONE
Depth-Driller	6000 ft
Depth-Logger	6000 ft
Bottom Log Interval	6000 ft
Top Log Interval	2500 ft
Casing-Driller	8 5/8 @ 2500 ft
Casing-Logger	2500 ft
Bit Size	7 7/8 in
Type Fluid in Hole	Gel Chem
Density	9.0 lb/gal
Viscosity	45 s
PH	10.0
Fluid Loss	6.0 cc
Source of Sample	Flowline
Rm @ Meas. Temp.	0.75 @ 75 °F
Rmf @ Meas. Temp.	0.60 @ 75 °F
Rmc @ Meas. Temp.	1.00 @ 75 °F
Rm @ BHT	0.40 @ 150 °F
Time Since Circulation	12 hrs
Time Since Cement	24 hrs
Max. Rec. Temp.	150 °F
Equipment Location	Ponca City, Oklahoma
Recorded By	Smith
Witnessed By	Jones

DUAL INDUCTION-SPHERICALLY FOCUSED LOG
COMPENSATED NEUTRON-LITHO DENSITY
HIGH RESOLUTION DIPMETER

COMPANY

KAISER-FRANCIS OIL CO.
WILDCAT
GRANT COUNTY, OKLAHOMA
OTHER SERVICES
DIL, BHC, CDL, CNL, HRD

5" CDL/SWN SECTION

Company	Kaiser-Francis Oil Co.		
Well	Wildcat		
Field			
County	Grant		
State	Oklahoma		
Permanent Datum	Ground Level	Elevation	3600 ft
Log Measured From	Kelly Bushing		14 ft above Perm. Datum
Drilling Measured From	Kelly Bushing		
Run Number	ONE	Date	1-Jan-1900
Depth-Driller	6000 ft	Bottom Log Interval	6000 ft
Depth-Logger	6000 ft	Top Log Interval	2500 ft
Casing-Driller	8 5/8 @ 2500 ft	Casing-Logger	2500 ft
Bit Size	7 7/8 in	Type Fluid in Hole	Gel Chem
Density	9.0 lb/gal	Viscosity	45 s
PH	10.0	Fluid Loss	6.0 cc
Source of Sample	Flowline		
Rm @ Meas. Temp.	0.75 @ 75 °F	Rmf @ Meas. Temp.	0.60 @ 75 °F
Rmc @ Meas. Temp.	1.00 @ 75 °F	Rm @ BHT	0.40 @ 150 °F
Time Since Circulation	12 hrs	Time Since Cement	24 hrs
Max. Rec. Temp.	150 °F	Equipment Location	Ponca City, Oklahoma
Recorded By	Smith	Witnessed By	Jones



5" CDL SECTION

Company	Kaiser-Francis Oil Co.		
Well	Wildcat		
Field			
County	Grant		
State	Oklahoma		
Permanent Datum	Ground Level	Elevation	3600 ft
Log Measured From	Kelly Bushing		14 ft above Perm. Datum
Drilling Measured From	Kelly Bushing		
Run Number	ONE	Date	1-Jan-1900
Depth-Driller	6000 ft	Bottom Log Interval	6000 ft
Depth-Logger	6000 ft	Top Log Interval	2500 ft
Casing-Driller	8 5/8 @ 2500 ft	Casing-Logger	2500 ft
Bit Size	7 7/8 in	Type Fluid in Hole	Gel Chem
Density	9.0 lb/gal	Viscosity	45 s
PH	10.0	Fluid Loss	6.0 cc
Source of Sample	Flowline		
Rm @ Meas. Temp.	0.75 @ 75 °F	Rmf @ Meas. Temp.	0.60 @ 75 °F
Rmc @ Meas. Temp.	1.00 @ 75 °F	Rm @ BHT	0.40 @ 150 °F
Time Since Circulation	12 hrs	Time Since Cement	24 hrs
Max. Rec. Temp.	150 °F	Equipment Location	Ponca City, Oklahoma
Recorded By	Smith	Witnessed By	Jones



25" HR CDL SECTION

Company	Kaiser-Francis Oil Co.		
Well	Wildcat		
Field			
County	Grant		
State	Oklahoma		
Permanent Datum	Ground Level	Elevation	3600 ft
Log Measured From	Kelly Bushing		14 ft above Perm. Datum
Drilling Measured From	Kelly Bushing		
Run Number	ONE	Date	1-Jan-1900
Depth-Driller	6000 ft	Bottom Log Interval	6000 ft
Depth-Logger	6000 ft	Top Log Interval	2500 ft
Casing-Driller	8 5/8 @ 2500 ft	Casing-Logger	2500 ft
Bit Size	7 7/8 in	Type Fluid in Hole	Gel Chem
Density	9.0 lb/gal	Viscosity	45 s
PH	10.0	Fluid Loss	6.0 cc
Source of Sample	Flowline		
Rm @ Meas. Temp.	0.75 @ 75 °F	Rmf @ Meas. Temp.	0.60 @ 75 °F
Rmc @ Meas. Temp.	1.00 @ 75 °F	Rm @ BHT	0.40 @ 150 °F
Time Since Circulation	12 hrs	Time Since Cement	24 hrs
Max. Rec. Temp.	150 °F	Equipment Location	Ponca City, Oklahoma
Recorded By	Smith	Witnessed By	Jones



Depth-Driller	6000 ft	Bottom Log Interval	6000 ft
Depth-Logger	6000 ft	Top Log Interval	2500 ft
Casing-Driller	8 5/8 @ 2500 ft	Casing-Logger	2500 ft

Scale	Line No.	Description	Line No.	Scale	Line No.	Scale
2"	1	SWN PAD CALIPER	2	2"	3	2"
5"	4					
5"	5	DIL DIFL-SFL	6	5"	7	5"
5"	8					
5"	9	CDL/CNL LITHO DENSITY-CNL	10	5"	11	5"
5"	12					

Kaiser-Francis Oil Co.
Wildcat
Grant County, Oklahoma
Schlumberger
Dual Induction-Spherically Focused Log
Compensated Neutron-Litho Density
High Resolution Dipmeter