Company: ACS CAMERON, INC.
Contractor: Nabors Drilling USA, Inc. Rig 112
Country: MEXICO
Field: ARENQUE
Well: ARENQUE 1
Section: 1
Township: 13 S
Range: 18 E
Permanent Datum: MEAN SEA LEVEL
Elevation: 0.00 m
Log Measured From: KELLY BUSHING
Drilling Measured From: KELLY BUSHING
Elevation: 0.00 m
Elevation: 0.00 m
Elevation: 0.00 m
Date: 30-Mar-2010
Run Number: ONE
Depth Driller: 3,000.00 m
Depth Logger: 3,000.00 m
Bottom Logged Interval: 2,999.00 m
Top Logged Interval: 2,000.00 m
Casing Driller: 2,000.00 m @ 0.00 m
Casing Logger: 2,000.00 m @ 0.00 m
Bit Size: 311.1 mm
Type Fluid in Hole: WBM
Density: 1.20 g/cm3
Viscosity: 0.00 s
PH: 0.00
Fluid Loss: 0.00 cm3
Source of Sample: FLOWLINE
Rm @ Measured Temp: 0.00 ohm-m @ 0.00 °C
Rmf @ Measured Temp: 0.00 ohm-m @ 0.00 °C
Rmc @ Measured Temp: 0.00 ohm-m @ 0.00 °C
Source of Rmf/Rmc: MEASURED
Rm @ BHT: 0.00 ohm-m @ 0.00 °C
Time Circulation Stopped: 00:00
Time Logger on Bottom: 00:00
Maximum Recorded Temp: 0.00 °C
Equipment / Base: 0000 / Ciudad del Carmen
Recorded By: Hector Cabrera / Jose Luis Lopez / Israel
Witnessed By: Jorge Ramirez
CAMERON
ACS
DUAL LATEROLOG
GAMMA RAY
SPONTANEOUS POTENTIAL
CABLE SPEED
CALIPER
BOREHOLE GEOMETRY
GAMMA RAY
CABLE SPEED
DUAL LATEROLOG
SPONTANEOUS POTENTIAL
CALIPER
BOREHOLE GEOMETRY
DUAL LATEROLOG
GAMMA RAY