

STATE OF MISSOURI



DEPARTMENT OF NATURAL RESOURCES

MISSOURI AIR CONSERVATION COMMISSION

PERMIT TO CONSTRUCT

Under the authority of RSMo 643 and the Federal Clean Air Act the applicant is authorized to construct the air contaminant source(s) described below, in accordance with the laws, rules and conditions as set forth herein.

Permit Number:

06 2016 - 008

Project Number: 2016-03-030

Installation ID: 065-0045

Parent Company: Rolla Ready Mix

Parent Company Address: P.O. Box 440459, St. Louis, MO 63144

Installation Name: Dent County Concrete - Salem Plant


Installation Address: 1351 East Scenic Rivers Blvd, Salem, MO 65560


Location Information: Dent County, S20 T34N R5W

Application for Authority to Construct was made for:
New stationary truck mix concrete plant. This review was conducted in accordance with Section (5), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*.

Standard Conditions (on reverse) are applicable to this permit.

Standard Conditions (on reverse) and Special Conditions are applicable to this permit.


Prepared by
Chad Stephenson
New Source Review Unit


Director or Designee
Department of Natural Resources
JUN 14 2016

Effective Date

STANDARD CONDITIONS:

Permission to construct may be revoked if you fail to begin construction or modification within two years from the effective date of this permit. Permittee should notify the Enforcement and Compliance Section of the Air Pollution Control Program if construction or modification is not started within two years after the effective date of this permit, or if construction or modification is suspended for one year or more.

You will be in violation of 10 CSR 10-6.060 if you fail to adhere to the specifications and conditions listed in your application, this permit and the project review. In the event that there is a discrepancy between the permit application and this permit, the conditions of this permit shall take precedence. Specifically, all air contaminant control devices shall be operated and maintained as specified in the application, associated plans and specifications.

You must notify the Enforcement and Compliance Section of the Department's Air Pollution Control Program of the anticipated date of start up of this (these) air contaminant source(s). The information must be made available within 30 days of actual startup. Also, you must notify the Department's regional office responsible for the area within which you are located within 15 days after the actual start up of this (these) air contaminant source(s).

A copy of the permit application and this permit and permit review shall be kept at the installation address and shall be made available to Department's personnel upon request.

You may appeal this permit or any of the listed special conditions to the Administrative Hearing Commission (AHC), P.O. Box 1557, Jefferson City, MO 65102, as provided in RSMo 643.075.6 and 621.250.3. If you choose to appeal, you must file a petition with the AHC within 30 days after the date this decision was mailed or the date it was delivered, whichever date was earlier. If any such petition is sent by registered mail or certified mail, it will be deemed filed on the date it is mailed. If it is sent by any method other than registered mail or certified mail, it will be deemed filed on the date it is received by the AHC.

If you choose not to appeal, this certificate, the project review and your application and associated correspondence constitutes your permit to construct. The permit allows you to construct and operate your air contaminant source(s), but in no way relieves you of your obligation to comply with all applicable provisions of the Missouri Air Conservation Law, regulations of the Missouri Department of Natural Resources and other applicable federal, state and local laws and ordinances.

The Air Pollution Control Program invites your questions regarding this air pollution permit. Please contact the Construction Permit Unit using the contact information below.

Contact Information:
Missouri Department of Natural Resources
Air Pollution Control Program
P.O. Box 176
Jefferson City, MO 65102-0176
(573) 751-4817

The regional office information can be found at the following website:
<http://dnr.mo.gov/regions/>

SITE SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

The special conditions listed in this permit were included based on the authority granted the Missouri Air Pollution Control Program by the Missouri Air Conservation Law (specifically 643.075) and by the Missouri Rules listed in Title 10, Division 10 of the Code of State Regulations (specifically 10 CSR 10-6.060). For specific details regarding conditions, see 10 CSR 10-6.060 paragraph (12)(A)10. "Conditions required by permitting authority."

1. Best Management Practices Requirement
Dent County Concrete - Salem Plant shall control fugitive emissions from all of the haul roads and vehicular activity areas at this site by performing BMPs as defined in Attachment AA.
2. Ambient Air Impact Limitation
 - A. Dent County Concrete - Salem Plant shall not cause an exceedance of the NAAQS for PM₁₀ of 150.0 µg/m³ 24-hour average in ambient air.
 - B. Dent County Concrete - Salem Plant shall demonstrate compliance with Special Condition 2.A using Attachment A or other equivalent forms that have been approved by the Air Pollution Control Program, including electronic forms. Dent County Concrete - Salem Plant shall account for the impacts from other sources of PM₁₀ as instructed in the attachments.
3. Moisture Content Testing Requirement
 - A. Dent County Concrete - Salem Plant shall verify that the moisture content of the processed rock is greater than or equal to 1.5 percent by weight.
 - B. Testing shall be conducted according to the method prescribed by the American Society for Testing Materials (ASTM) D-2216, C-566 or another method approved by the Director.
 - C. The initial test shall be conducted no later than 45 days after the start of operation. A second test shall be performed the calendar year following the initial test during the months of July or August.
 - D. The test samples shall be taken from rock that has been processed by the plant or from each source of aggregate (e.g. quarry).
 - E. The written analytical report shall include the raw data and moisture content of each sample, the test date and the original signature of the individual performing the test. The report shall be filed on-site or at the Dent County Concrete - Salem Plant main office within 30 days of completion of the required test.
 - F. If the moisture content of either of the two tests is less than the moisture content in Special Condition 3.A, another test may be performed within 15 days of the

SITE SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

noncompliant test. If the results of that test is less than the moisture content in Special Condition 3.A, Dent County Concrete - Salem Plant shall either:

- 1) Apply for a new permit to account for the revised information, or
- 2) Submit a plan for the installation of wet spray devices to the Compliance/Enforcement Section of the Air Pollution Control Program within 10 days of the second noncompliant test. The wet spray devices shall be installed and operational within 40 days of the second noncompliant test.

- G. In lieu of testing, Dent County Concrete - Salem Plant may obtain test results that demonstrate compliance with the moisture content in Special Condition 3.A from the supplier of the aggregate.

4. Control Device Requirement-Baghouse

- A. Dent County Concrete - Salem Plant shall control emissions from the equipment listed below using baghouses as specified in the permit application.

- 1) Cement Silo
- 2) Supplement Silo
- 3) Weigh Hopper
- 4) Truck Mix Loadout (shroud vented to baghouse)

- B. The baghouses shall be operated and maintained in accordance with the manufacturer's specifications. The baghouse shall be equipped with a gauge or meter, which indicates the pressure drop across the control device. These gauges or meters shall be located such that Department of Natural Resources' employees may easily observe them.

- C. Replacement filters for the baghouses shall be kept on hand at all times. The bags shall be made of fibers appropriate for operating conditions expected to occur (i.e. temperature limits, acidic and alkali resistance, and abrasion resistance).

- D. Dent County Concrete - Salem Plant shall monitor and record the operating pressure drop across the baghouses at least once every 24 hours. The operating pressure drop shall be maintained within the design conditions specified by the manufacturer's performance warranty.

- E. Dent County Concrete - Salem Plant shall maintain a copy of the baghouse manufacturer's performance warranty on site.

- F. Dent County Concrete - Salem Plant shall maintain an operating and maintenance log for the baghouses which shall include the following:

SITE SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

- 1) Incidents of malfunction, with impact on emissions, duration of event, probable cause, and corrective actions; and
 - 2) Maintenance activities, with inspection schedule, repair actions, and replacements, etc.
-
5. **Minimum Distance to Property Boundary Requirement**
The primary emission point, aggregate transfer (EP-1), shall be located at least 100 feet from the nearest property boundary.
 6. **Concurrent Operation Restriction**
Dent County Concrete - Salem Plant is prohibited from operating whenever other plants are located at the site.
 7. **Record Keeping Requirement**
Dent County Concrete - Salem Plant shall maintain all records required by this permit for not less than five years and make them available to any Missouri Department of Natural Resources' personnel upon request.
 8. **Reporting Requirement**
Dent County Concrete - Salem Plant shall report to the Air Pollution Control Program, Enforcement Section, P.O. Box 176, Jefferson City, MO 65102, no later than 10 days after any exceedances of the limitations imposed by this permit.

REVIEW OF APPLICATION FOR AUTHORITY TO CONSTRUCT AND OPERATE
SECTION (5) REVIEW

Project Number: 2016-03-030
Installation ID Number: 065-0045
Permit Number:

Dent County Concrete - Salem Plant
1351 East Scenic Rivers Blvd
Salem, MO 65560

Complete: March 17, 2016

Parent Company:
Rolla Ready Mix
P.O. Box 440459
St. Louis, MO 63144

Dent County, S20 T34N R5W

PROJECT DESCRIPTION

Dent County Concrete will be constructing a ready-mix concrete batch plant consisting of a 1992 Ross – Bandit. It is a 12-yard truck-mix plant rated at 200 tons per hour. Stone will be delivered to the site by end-dump trailers by a 390 feet long haul road. The plant will have two storage piles that are approximately 1600 square feet each. The plant will be powered off the grid.

The applicant is using one of the methods described in Attachment AA, “Best Management Practices,” to control emissions from haul roads and vehicular activity areas.

This installation is located in Dent County, an attainment area for all criteria pollutants..

This installation is not on the List of Named Installations found in 10 CSR 10-6.020(3)(B), Table 2. The installation's major source level is 250 tons per year and fugitive emissions are not counted toward major source applicability.

No permits have been issued to Dent County Concrete - Salem Plant from the Air Pollution Control Program.

TABLES

The table below summarizes the emissions of this project. The potential emissions of the process equipment, exclude emissions from haul roads and wind erosion. There are no existing actual emissions since this project is for a new plant. The potential emissions of the application represent the emissions of all equipment and activities

assuming continuous operation (8760 hours per year). The conditioned potential emissions represent the emissions after taking into account the reduction of annual emissions due to adhering to the 24-hour NAAQS for PM₁₀

Table 1: Emissions Summary (tons per year)

Air Pollutant	De Minimis Level/SMAL	^a Potential Emissions of Process Equipment	Existing Actual Emissions	^b Potential Emissions of the Application	Conditioned Potential Emissions
PM	25.0	6.68	N/A	27.98	14.09
PM ₁₀	15.0	3.00	N/A	10.75	5.41
PM _{2.5}	10.0	1.31	N/A	4.16	2.09
SO _x	40.0	N/A	N/A	N/A	N/A
NO _x	40.0	N/A	N/A	N/A	N/A
VOC	40.0	N/A	N/A	N/A	N/A
CO	100.0	N/A	N/A	N/A	N/A
Total HAPs	25.0	N/A	N/A	N/A	N/A

N/A = Not Applicable

^aExcludes haul road and storage pile emissions

^bIncludes site specific haul road and storage pile emissions

Table 2: Ambient Air Quality Impact Analysis

Pollutant	NAAQS/RAL (µg/m ³)	Averaging Time	^a Maximum Modeled Impact (µg/m ³)	Limited Impact (µg/m ³)	Background (µg/m ³)	^b Daily Limit (tons/day)
^c PM ₁₀ (solitary)	150.0	24-hour	298.19	130.00	20.0	2,416

^aModeled impact at maximum capacity with controls

^bIndirect limit based on compliance with NAAQS.

^cSolitary operation

EMISSIONS CALCULATIONS

Emissions for the project were calculated using emission factors found in the United States EPA document AP-42 *Compilation of Air Pollutant Emission Factors, Volume 1: Stationary Point and Area Sources*, Fifth Edition (AP-42).

Emissions from the concrete batch plant were calculated using emission factors from AP-42 Section 11.12 "Concrete Batching," June 2006. This section cites Equation (1) in Section 13.2.4 "Aggregate Handling and Storage Piles," November 2006 for calculating the emissions from aggregate and sand transfer. The cement and supplement silos are controlled with baghouses, so the controlled emission factors were used. Emissions from the aggregate weigh hopper were calculated using AP-42 Section 13.2.4, Equation (1). These emissions are controlled by a baghouse so a 99% control factor was applied to the calculation. Emissions from mix truck loading are controlled by a shroud vented to a baghouse, so the controlled emission factor was used.

Emissions from haul roads and vehicular activity areas were calculated using the predictive equation from AP-42 Section 13.2.2 "Unpaved Roads," November 2006. A 90% control efficiency for PM and PM₁₀ and a 40% control efficiency for PM_{2.5} were applied to the emission calculations for the use of BMPs. Emissions from load-in and load-out of storage piles were calculated using the predictive equation from AP-42 Section 13.2.4. The moisture content of the aggregate is 1.5% by weight. Emissions from wind erosion of storage piles were calculated using an equation found in the Air Pollution Control Program's Emissions Inventory Questionnaire Form 2.8 "Storage Pile Worksheet."

AMBIENT AIR QUALITY IMPACT ANALYSIS

An ambient air quality impact analysis (AAQIA) was performed to determine the impact of the pollutants listed in Table 2. The Air Pollution Control Program requires an AAQIA of PM₁₀ for all asphalt, concrete and rock-crushing plants regardless of the level of PM₁₀ emissions if a permit is required. An AAQIA is required for other pollutants if their emissions exceed their respective de minimis or screening model action level (SMAL). The AAQIA was performed using the Air Pollution Control Program's generic nomographs and when appropriate the EPA modeling software AERSCREEN. For each pollutant that was modeled, the maximum concentration that occurs at or beyond the site boundary was compared to the NAAQS or RAL for the pollutant. If during continuous operation the modeled concentration of a pollutant is greater than the applicable NAAQS or RAL, the plant's production is limited to ensure compliance with the standard.

This plant uses BMPs to control emissions from haul roads and vehicular activity areas, so emissions from these sources were not included in the AAQIA. Instead they were addressed as a background concentration of 20 µg/m³ of PM₁₀ in accordance with the Air Pollution Control Program's BMPs interim policy.

PERMIT RULE APPLICABILITY

This review was conducted in accordance with Section (5) of Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*. Potential emissions of PM are above the de minimis level but remain below the major source level.

APPLICABLE REQUIREMENTS

Dent County Concrete - Salem Plant shall comply with the following applicable requirements. The Missouri Air Conservation Laws and Regulations should be consulted for specific record keeping, monitoring, and reporting requirements. Compliance with these emission standards, based on information submitted in the application, has been verified at the time this application was approved.

GENERAL REQUIREMENTS

- *Submission of Emission Data, Emission Fees and Process Information*, 10 CSR 10-6.110.
- *Restriction of Particulate Matter to the Ambient Air Beyond the Premises of Origin*, 10 CSR 10-6.170
- *Restriction of Emission of Visible Air Contaminants*, 10 CSR 10-6.220
- No Operating Permit is required for this installation
- *Restriction of Emission of Odors*, 10 CSR 10-6.165

SPECIFIC REQUIREMENTS

- *Restriction of Emission of Particulate Matter From Industrial Processes*, 10 CSR 10-6.400
- None of the National Emission Standards for Hazardous Air Pollutants (NESHAPS) or National Emission Standards for Hazardous Air Pollutants for Source Categories (MACTS) apply to the proposed equipment.

STAFF RECOMMENDATION

On the basis of this review conducted in accordance with Section (5), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*, it is recommended that this permit be granted with special conditions.

PERMIT DOCUMENTS

The following documents are incorporated by reference into this permit:

- The Application for Authority to Construct form, dated March 7, 2016, received March 14, 2016, designating Rolla Ready Mix as the owner and operator of the installation.

Attachment AA: Best Management Practices

Haul roads and vehicular activity areas shall be maintained in accordance with at least one of the following options when the plant is operating.

1. Pavement
 - A. The operator shall pave the area with materials such as asphalt, concrete or other materials approved by the Air Pollution Control Program. The pavement will be applied in accordance with industry standards to achieve control of fugitive emissions while the plant is operating.
 - B. Maintenance and repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator shall periodically wash or otherwise clean all of the paved portions of the haul roads as necessary to achieve control of fugitive emissions from these areas while the plant is operating.

2. Application of Chemical Dust Suppressants
 - A. The operator shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to unpaved areas.
 - B. The quantities of the chemical dust suppressant shall be applied and maintained in accordance with the manufacturer's recommendation (if available) and in sufficient quantities to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator shall keep these records with the plant for not less than five (5) years and make these records available to Department of Natural Resources' personnel upon request.

3. Application of Water-Documented Daily
 - A. The operator shall apply water to unpaved areas. Water shall be applied at a rate of 100 gallons per day per 1,000 square feet of unpaved or untreated surface area while the plant is operating.
 - B. Precipitation may be substituted for watering if the precipitation is greater than one quarter of one inch and is sufficient to control fugitive emissions.
 - C. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads.
 - D. The operator shall record the date, volume of water application and total surface area of active haul roads or the amount of precipitation that day. The operators shall also record the rationale for not watering (e.g. freezing conditions or not operating).
 - E. The operator shall keep these records with the plant for not less than five (5) years, and the operator shall make these records available to Department of Natural Resources' personnel upon request.

APPENDIX A

Abbreviations and Acronyms

%	percent	MMBtu	Million British thermal units
°F	degrees Fahrenheit	MMCF	million cubic feet
acfm	actual cubic feet per minute	MSDS	Material Safety Data Sheet
BACT	Best Available Control Technology	NAAQS ...	National Ambient Air Quality Standards
BMPs	Best Management Practices	NESHAPs ..	National Emissions Standards for Hazardous Air Pollutants
Btu	British thermal unit	NO_x	nitrogen oxides
CAM	Compliance Assurance Monitoring	NSPS	New Source Performance Standards
CAS	Chemical Abstracts Service	NSR	New Source Review
CEMS	Continuous Emission Monitor System	PM	particulate matter
CFR	Code of Federal Regulations	PM_{2.5}	particulate matter less than 2.5 microns in aerodynamic diameter
CO	carbon monoxide	PM₁₀	particulate matter less than 10 microns in aerodynamic diameter
CO₂	carbon dioxide	ppm	parts per million
CO_{2e}	carbon dioxide equivalent	PSD	Prevention of Significant Deterioration
COMS	Continuous Opacity Monitoring System	PTE	potential to emit
CSR	Code of State Regulations	RACT	Reasonable Available Control Technology
dscf	dry standard cubic feet	RAL	Risk Assessment Level
EQ	Emission Inventory Questionnaire	SCC	Source Classification Code
EP	Emission Point	scfm	standard cubic feet per minute
EPA	Environmental Protection Agency	SDS	Safety Data Sheet
EU	Emission Unit	SIC	Standard Industrial Classification
fps	feet per second	SIP	State Implementation Plan
ft	feet	SMAL	Screening Model Action Levels
GACT	Generally Available Control Technology	SO_x	sulfur oxides
GHG	Greenhouse Gas	SO₂	sulfur dioxide
gpm	gallons per minute	tph	tons per hour
gr	grains	tpy	tons per year
GWP	Global Warming Potential	VMT	vehicle miles traveled
HAP	Hazardous Air Pollutant	VOC	Volatile Organic Compound
hr	hour		
hp	horsepower		
lb	pound		
lbs/hr	pounds per hour		
MACT	Maximum Achievable Control Technology		
µg/m³	micrograms per cubic meter		
m/s	meters per second		
Mgal	1,000 gallons		
MW	megawatt		
MHDR	maximum hourly design rate		

Mr. Bill Beistel
Operations Manager
Dent County Concrete - Salem Plant
P.O. Box 440459
St. Louis, MO 63144

RE: New Source Review Permit - Project Number: 2016-03-030

Dear Mr. Beistel:

Enclosed with this letter is your permit to construct. Please study it carefully and refer to Appendix A for a list of common abbreviations and acronyms used in the permit. Also, note the special conditions on the accompanying pages. The document entitled, "Review of Application for Authority to Construct," is part of the permit and should be kept with this permit in your files. Operation in accordance with these conditions and your new source review permit application is necessary for continued compliance. The reverse side of your permit certificate has important information concerning standard permit conditions and your rights and obligations under the laws and regulations of the State of Missouri.

This permit may include requirements with which you may not be familiar. If you would like the department to meet with you to discuss how to understand and satisfy the requirements contained in this permit, an appointment referred to as a Compliance Assistance Visit (CAV) can be set up with you. To request a CAV, please contact your local regional office or fill out an online request. The regional office contact information can be found at the following website:

<http://dnr.mo.gov/regions/>. The online CAV request can be found at <http://dnr.mo.gov/cav/compliance.htm>.

If you were adversely affected by this permit decision, you may be entitled to pursue an appeal before the administrative hearing commission pursuant to Sections 621.250 and 643.075.6 RSMo. To appeal, you must file a petition with the administrative hearing commission within thirty days after the date this decision was mailed or the date it was delivered, whichever date was earlier. If any such petition is sent by registered mail or certified mail, it will be deemed filed on the date it is mailed; if it is sent by any method other than registered mail or certified mail, it will be deemed filed on the date it is received by the administrative hearing commission, whose contact information is: Administrative Hearing Commission, United States Post Office Building, 131 West High Street, Third Floor, P.O. Box 1557, Jefferson City, Missouri 65102, phone: 573-751-2422, fax: 573-751-5018, website: www.oa.mo.gov/ahc.

Mr. Bill Beistel
Page Two

If you have any questions regarding this permit, please do not hesitate to contact Chad Stephenson, at the department's Air Pollution Control Program, P.O. Box 176, Jefferson City, MO 65102 or at (573) 751-4817. Thank you for your attention to this matter.

Sincerely,

AIR POLLUTION CONTROL PROGRAM

Susan Heckenkamp
New Source Review Unit Chief

SH:csj

Enclosures

c: Southeast Regional Office
PAMS File: 2016-03-030

Permit Number: