

PERMIT BOOK

STATE OF MISSOURI



DEPARTMENT OF NATURAL RESOURCES

MISSOURI AIR CONSERVATION COMMISSION

PERMIT TO CONSTRUCT

Under the authority of RSMo 643 and the Federal Clean Air Act the applicant is authorized to construct the air contaminant source(s) described below, in accordance with the laws, rules and conditions as set forth herein.

Permit Number: 022010-007

Project Number: 2009-10-049

Parent Company: Table Rock Asphalt Construction Company Inc.

Parent Company Address: P.O. Box 1165, Branson, MO 65616

Installation Name: Southwest Materials

Installation ID: PORT-0659

Installation Address: 1/4 mile West of Hwy CC and HWY 65, Ozark, MO 65721

Location Information: Christian County, S27, T4N, R21W

Application for Authority to Construct was made for:
a new portable truck mix concrete plant. This review was conducted in accordance with
Section (5), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*.

Standard Conditions (on reverse) are applicable to this permit.

Standard Conditions (on reverse) and Special Conditions are applicable to this permit.

FEB 22 2010

EFFECTIVE DATE

A handwritten signature in black ink, appearing to read "James K. Kawenczyk".
DIRECTOR OR DESIGNEE
DEPARTMENT OF NATURAL RESOURCES

STANDARD CONDITIONS:

Permission to construct may be revoked if you fail to begin construction or modification within two years from the effective date of this permit. Permittee should notify the Air Pollution Control Program if construction or modification is not started within two years after the effective date of this permit, or if construction or modification is suspended for one year or more.

You will be in violation of 10 CSR 10-6.060 if you fail to adhere to the specifications and conditions listed in your application, this permit and the project review. In the event that there is a discrepancy between the permit application and this permit, the conditions of this permit shall take precedence. Specifically, all air contaminant control devices shall be operated and maintained as specified in the application, associated plans and specifications.

You must notify the Departments' Air Pollution Control Program of the anticipated date of start up of this (these) air contaminant source(s). The information must be made available within 30 days of actual startup. Also, you must notify the Department of Natural Resources Regional office responsible for the area within which you are located within 15 days after the actual start up of this (these) air contaminant source(s).

A copy of this permit and permit review shall be kept at the installation address and shall be made available to Department of Natural Resources' personnel upon request.

You may appeal this permit or any of the listed special conditions to the Administrative Hearing Commission (AHC), P.O. Box 1557, Jefferson City, MO 65102, as provided in RSMo 643.075.6 and 621.250.3. If you choose to appeal, you must file a petition with the AHC within 30 days after the date this decision was mailed or the date it was delivered, whichever date was earlier. If any such petition is sent by registered mail or certified mail, it will be deemed filed on the date it is mailed. If it is sent by any method other than registered mail or certified mail, it will be deemed filed on the date it is received by the AHC.

If you choose not to appeal, this certificate, the project review and your application and associated correspondence constitutes your permit to construct. The permit allows you to construct and operate your air contaminant source(s), but in no way relieves you of your obligation to comply with all applicable provisions of the Missouri Air Conservation Law, regulations of the Missouri Department of Natural Resources and other applicable federal, state and local laws and ordinances.

The Air Pollution Control Program invites your questions regarding this air pollution permit. Please contact the Construction Permit Unit at (573) 751-4817. If you prefer to write, please address your correspondence to the Missouri Department of Natural Resources, Air Pollution Control Program, P.O. Box 176, Jefferson City, MO 65102-0176, attention: Construction Permit Unit.

Page No.	3
Permit No.	
Project No.	2009-10-049

GENERAL SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

The special conditions listed in this permit were included based on the authority granted the Missouri Air Pollution Control Program by the Missouri Air Conservation Law (specifically 643.075) and by the Missouri Rules listed in Title 10, Division 10 of the Code of State Regulations (specifically 10 CSR 10-6.060). For specific details regarding conditions, see 10 CSR 10-6.060 paragraph (12)(A)10. "Conditions required by permitting authority."

1. Equipment Identification Requirement
Southwest Materials shall maintain easily read permanent markings on each component of the plant. These markings shall be the equipment's serial number or a company assigned identification number that uniquely identifies the individual component.

2. Relocation of Portable Concrete Plant
 - A. Southwest Materials' PORT 0659 shall not be operated at any location longer than 24 consecutive months.

 - B. A complete "Portable Source Relocation Request" application must be submitted to the Air Pollution Control Program prior to any relocation of this portable concrete plant.
 - 1.) If the portable concrete plant is moving to a site previously permitted, and if the circumstances at the site have not changed, then the application must be received by the Air Pollution Control Program at least seven days prior to the relocation.
 - 2.) If the portable concrete plant is moving to a new site, or if circumstances at the site have changed (e.g. the site was only permitted for solitary operation and now another plant is located at the site), then the application must be received by the Air Pollution Control Program at least 21 days prior to the relocation. The application must include written notification of any concurrently operating plants.

Page No.	4
Permit No.	
Project No.	2009-10-049

SITE SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

The special conditions listed in this permit were included based on the authority granted the Missouri Air Pollution Control Program by the Missouri Air Conservation Law (specifically 643.075) and by the Missouri Rules listed in Title 10, Division 10 of the Code of State Regulations (specifically 10 CSR 10-6.060). For specific details regarding conditions, see 10 CSR 10-6.060 paragraph (12)(A)10. "Conditions required by permitting authority."

PORT ID Number: PORT-0659

Site ID Number: 043-0025

Site Name: Southwest Materials

Site Address: 1/4 mile West of Hwy CC and HWY 65 Ozark, MO 65721

Site County: Christian S27, T4N, R21W

1. Best Management Practices Requirement
Southwest Materials shall control fugitive emissions from all of the haul roads and vehicular activity areas at this site by performing Best Management Practices as defined in Attachment AA.
2. Ambient Air Impact Limitation
 - A. Southwest Materials shall not cause an exceedance of the National Ambient Air Quality Standard (NAAQS) for particulate matter less than ten microns in aerodynamic diameter (PM₁₀) of 150.0 µg/m³ 24-hour average in ambient air.
 - B. Southwest Materials shall demonstrate compliance with special condition 2.A. using Attachment A or another equivalent form that has been approved by the Air Pollution Control Program, including an electronic form.
3. Control Device Requirement-Baghouse
 - A. Southwest Materials shall control emissions from the equipment listed below using baghouses as specified in the permit application.
 - 1.) Cement Silo
 - 2.) Supplement Silo
 - 3.) Weigh Hopper
 - 4.) Truck Mix Loadout (shroud vented to baghouse)
 - B. The baghouses shall be operated and maintained in accordance with the manufacturer's specifications. The baghouse shall be equipped with a gauge or meter, which indicates the pressure drop across the control device. These gauges or meters shall be located such that the Department of Natural Resources employees may easily observe them.

Page No.	5
Permit No.	
Project No.	2009-10-049

SITE SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

- C. Replacement filters for the baghouses shall be kept on hand at all times. The bags shall be made of fibers appropriate for operating conditions expected to occur (i.e. temperature limits, acidic and alkali resistance, and abrasion resistance).
- D. Southwest Materials shall monitor and record the operating pressure drop across the baghouses at least once every 24 hours. The operating pressure drop shall be maintained within the design conditions specified by the manufacturer's performance warranty.
- E. Southwest Materials shall maintain an operating and maintenance log for the baghouses which shall include the following:
 - 1.) Incidents of malfunction, with impact on emissions, duration of event, probable cause, and corrective actions; and
 - 2.) Maintenance activities, with inspection schedule, repair actions, and replacements, etc.
- 4. Moisture Content Testing Requirement
 - A. Southwest Materials shall verify through testing that the moisture content of the processes rock is greater than or equal to 3.0% weight.
 - B. Testing shall be conducted according to the method prescribed by the American Society for Testing Materials (ASTM) D-2216, C-566 or another method approved by the Director.
 - C. The initial test shall be conducted within 45 days after the start of operation. A second test shall be performed the calendar year following the initial test during the months of July or August.
 - D. The test samples shall be taken from rock that has been processed by the plant or from each source (e.g. quarry) of aggregate.
 - E. The written analytical report shall include the raw data and moisture content of each sample, the test date and the original signature of the individual performing the test. The report shall be filed on-site or at the main office within 30 days of completion of the required test.
 - F. If the moisture content of either of the two tests is less than the moisture content in special condition 4.A, another test may be performed with 15 days of the noncompliant test. If the results of that test also exceed the limit, Southwest Materials shall either:
 - 1.) Apply for a new permit to account for the revised information, or

Page No.	6
Permit No.	
Project No.	2009-10-049

SITE SPECIFIC SPECIAL CONDITIONS:

The permittee is authorized to construct and operate subject to the following special conditions:

- 2.) Submit a plan for the installation of wet spray devices to the Air Pollution Control Program Compliance Assistance section within 10 days of the second noncompliant test. The wet spray devices shall be installed and operational within 40 days of the second noncompliant test.
 - G. In lieu of testing, Southwest Materials may obtain test results from the supplier of the aggregate that demonstrate compliance with the moisture content in special condition 4.A.
5. Minimum Distance to Property Boundary Requirement
The primary emission point shall be located at least 200 feet from the nearest property boundary.
6. Concurrent Operation
No other plants are allowed to operate while PORT-0659 is located at this site.
7. Record Keeping Requirement
Southwest Materials shall maintain all records required by this permit for five years and make them available to any Missouri Department of Natural Resources personnel upon request.
8. Reporting Requirement
Southwest Materials shall report to the Air Pollution Control Program Enforcement Section P.O. Box 176, Jefferson City, MO 65102, no later than ten days after any exceedances of the limitations imposed by this permit.

REVIEW OF APPLICATION FOR AUTHORITY TO CONSTRUCT AND OPERATE
SECTION (5) REVIEW

Project Number: 2009-10-049
Installation ID Number: PORT-0659
Permit Number:

Southwest Materials
1/4 mile West of Hwy CC and HWY 65
Ozark, MO 65721

Complete: October 22, 2009

Parent Company:
Table Rock Asphalt Construction Company Inc.
P.O. Box 1165
Branson, MO 65616

Christian County, S27, T4N, R21W

PROJECT DESCRIPTION

Southwest Materials is constructing a new portable truck mix concrete plant for concurrent location with its existing stationary concrete truck mix concrete plant. However, the existing stationary plant will not be allowed to operate while the two plants are co-located. The new portable plant can produce 200 tons of concrete per hour. It is powered by electricity from the grid. Cement and fly ash silos are controlled by baghouses, as well as the weigh hopper and truck mix loading.

The applicant is using one of the methods described in Attachment AA, "Best Management Practices," to control emissions from haul roads and vehicular activity areas. This installation is located in Christian County, an attainment area for all criteria pollutants. This installation is not on the List of Named Installations found in 10 CSR 10-6.020(3)(B), Table 2. The installation's major source level is 250 tons per year and fugitive emissions are not counted toward major source applicability. No permits have been issued for PORT-0659 to Southwest Materials from the Air Pollution Control Program. The installation is currently permitted under construction permit 0795-020 and basic operating permit project number 2009-04-063. As the existing installation is limited to below de minimis levels and no NSPS, MACT, or NESHAP applies, it does not need an operating permit.

TABLES

The table below summarizes the emissions of this project. The potential emissions of process equipment excluding emissions from haul roads and wind erosion, which are site specific, should not vary from site to site. The uncontrolled potential emissions of the application exclude baghouses and BMPs. The controlled potential emissions of the application represent the emissions of all equipment and activities assuming continuous operation (8760 hours per year). The conditioned potential emissions represent an indirect limit by performing an ambient air quality impact analysis.

Table 1: Emissions Summary (tons per year)

Air Pollutant	De Minimis Level/ SMAL	¹ Potential Emissions of the Process Equipment	² Uncontrolled Potential Emissions of the Application	³ Controlled Potential Emissions of the Application	Conditioned Potential Emissions
PM ₁₀	15.0	3.04	106.85	6.68	5.58
SO _x	40.0	N/A	N/A	N/A	N/A
NO _x	40.0	N/A	N/A	N/A	N/A
VOC	40.0	N/A	N/A	N/A	N/A
CO	100.0	N/A	N/A	N/A	N/A
Total HAPs	25.0	N/A	N/A	N/A	N/A

N/A = Not Applicable

¹Excludes haul road and wind erosion emissions. Includes baghouses.

²Includes haul road and wind erosion emissions. Excludes baghouses.

³Includes site specific haul road and storage pile emissions. Includes baghouses.

Table 2: Ambient Air Quality Impact Analysis

Pollutant	¹ NAAQS (µg/m ³)	Averaging Time	² Maximum Modeled Impact (µg/m ³)	Limited Impact (µg/m ³)	Background (µg/m ³)	³ Daily Limit (tons/day)
⁴ PM ₁₀	150.0	24-hour	169.74	130.0	20.0	4,010

¹National Ambient Air Quality Standards (NAAQS)

²Modeled impact at maximum capacity with controls.

³Indirect limit based on compliance with NAAQS.

⁴Solitary operation.

EMISSIONS CALCULATIONS

Emissions for the project were calculated using emission factors found in the United States Environmental Protection Agency (EPA) document AP-42 *Compilation of Air Pollutant Emission Factors, Volume 1: Stationary Point and Area Sources*, Fifth Edition (AP-42).

Emissions from the concrete batch plant were calculated using emission factors from AP-42 Section 11.12 “Concrete Batching,” June 2006. This section cites Equation (1) in Section 13.2.4 “Aggregate Handling and Storage Piles,” November 2006 for calculating the emissions from aggregate and sand transfer. The cement and supplement silos are controlled with baghouses, so the controlled emission factors were used. Emissions from the aggregate weigh hopper were calculated using AP-42 Section 13.2.4, Equation (1). These emissions are controlled by a baghouse so a 99% control factor was applied to the calculation. Emissions from mix truck loading are controlled by a shroud vented to a baghouse, so the controlled emission factor was used.

Emissions from haul roads and vehicular activity areas were calculated using the predictive equation from AP-42 Section 13.2.2 “Unpaved Roads,” November 2006. A 95% control efficiency is applied to the emission calculations for the use of BMPs. Emissions from load-in and load-out of storage piles were calculated using the predictive equation from AP-42 Section 13.2.4 “Aggregate Handling and Storage Piles”. The moisture content of the aggregate is 3.0% weight. Emissions from wind erosion of storage piles were calculated using an equation found in the Air Pollution Control Program’s Emissions Inventory Questionnaire Form 2.8 “Storage Pile Worksheet.”

AMBIENT AIR QUALITY IMPACT ANALYSIS

An ambient air quality impact analysis (AAQIA) was performed to determine the impact of PM₁₀. The Air Pollution Control Program requires an AAQIA of PM₁₀ for all asphalt, concrete and rock-crushing plants regardless of the level of PM₁₀ emissions if a permit is required. The AAQIA was performed using the Air Pollution Control Program's generic nomographs. For each pollutant that was modeled, the maximum concentration that occurs at or beyond the site boundary was compared to the National Ambient Air Quality Standard (NAAQS) for the pollutant. The distance from the plant to the nearest site boundary is 200 feet. When the plant operates continuously, the modeled concentration of PM₁₀ is greater than the NAAQS, so the plant's production was limited to ensure compliance with the NAAQS.

This plant uses BMPs to control emissions from haul roads and vehicular activity areas, so emissions from these sources were not included in the AAQIA. Instead they were addressed as a background concentration of 20 µg/m³ of PM₁₀ in accordance with the Air Pollution Control Program's BMPs interim policy.

PERMIT RULE APPLICABILITY

This review was conducted in accordance with Section (5) of Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*. Potential emissions of PM₁₀ are conditioned below de minimis levels.

APPLICABLE REQUIREMENTS

Southwest Materials shall comply with the following applicable requirements. The Missouri Air Conservation Laws and Regulations should be consulted for specific record keeping, monitoring, and reporting requirements. Compliance with these emission standards, based on information submitted in the application, has been verified at the time this application was approved.

GENERAL REQUIREMENTS

- *Submission of Emission Data, Emission Fees and Process Information*, 10 CSR 10-6.110. The emission fee is the amount established by the Missouri Air Conservation Commission annually under Missouri Air Law 643.079(1). Submission of an Emissions Inventory Questionnaire (EIQ) is required June 1 for the previous year's emissions.
- No Operating Permit is required for PORT-0659 or this installation.
- *Restriction of Particulate Matter to the Ambient Air Beyond the Premises of Origin*, 10 CSR 10-6.170
- *Restriction of Emission of Visible Air Contaminants*, 10 CSR 10-6.220
- *Restriction of Emission of Odors*, 10 CSR 10-3.090

SPECIFIC REQUIREMENTS

- *Restriction of Emission of Particulate Matter From Industrial Processes*, 10 CSR 10-6.400
- None of the New Source Performance Standards (NSPS) apply to the installation.
- None of the National Emission Standards for Hazardous Air Pollutants (NESHAPS) or National Emission Standards for Hazardous Air Pollutants for Source Categories (MACTS) apply to the proposed equipment.

STAFF RECOMMENDATION

On the basis of this review conducted in accordance with Section (5), Missouri State Rule 10 CSR 10-6.060, *Construction Permits Required*, I recommend this permit be granted with special conditions.

David Little
Environmental Engineer

Date

PERMIT DOCUMENTS

The following documents are incorporated by reference into this permit:

- The Application for Authority to Construct form, dated October 20, 2009, received October 20, 2009, designating Table Rock Asphalt Construction Company Inc. as the owner and operator of the installation.
- U.S. EPA document AP-42, *Compilation of Air Pollutant Emission Factors*, Fifth Edition.
- Southwest Regional Office Site Survey, dated November 02, 2009.

Attachment AA: Best Management Practices

Haul roads and vehicular activity areas shall be maintained in accordance with at least one of the following options when the portable plant is operating.

1. Pavement
 - A. The operator shall pave the area with materials such as asphalt, concrete or other materials approved by the Air Pollution Control Program. The pavement will be applied in accordance with industry standards to achieve control of fugitive emissions¹ while the plant is operating.
 - B. Maintenance and repair of the road surface will be conducted as necessary to ensure that the physical integrity of the pavement is adequate to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator shall periodically wash or otherwise clean all of the paved portions of the haul roads as necessary to achieve control of fugitive emissions from these areas while the plant is operating.

2. Application of Chemical Dust Suppressants
 - A. The operator shall apply a chemical dust suppressant (such as magnesium chloride, calcium chloride, lignosulfonates, etc.) to unpaved areas.
 - B. The quantities of the chemical dust suppressant shall be applied and maintained in accordance with the manufacturer's recommendation (if available) and in sufficient quantities to achieve control of fugitive emissions from these areas while the plant is operating.
 - C. The operator shall record the time, date and the amount of material applied for each application of the chemical dust suppressant agent on the above areas. The operator shall keep these records with the plant for not less than five (5) years and make these records available to Department of Natural Resources personnel upon request.

3. Application of Water-Documented Daily
 - A. The operator shall apply water to unpaved areas. Water shall be applied at a rate of 100 gallons per day per 1,000 square feet of unpaved or untreated surface area while the plant is operating.
 - B. Precipitation may be substituted for watering if the precipitation is greater than one quarter of one inch and is sufficient to control fugitive emissions.
 - C. Watering may also be suspended when the ground is frozen, during periods of freezing conditions when watering would be inadvisable for traffic safety reasons, or when there will be no traffic on the roads.
 - D. The operator shall record the date, volume of water application and total surface area of active haul roads or the amount of precipitation that day. The operators shall also record the rationale for not watering (e.g. freezing conditions or not operating).
 - E. The operator shall keep these records with the plant for not less than five (5) years, and the operator shall make these records available to Department of Natural Resources personnel upon request

¹For purposes of this document, Control of Fugitive Emissions means to control particulate matter that is not collected by a capture system and visible emissions to the extent necessary to prevent violations of the air pollution law or regulation. (Note: control of visible emission is not the only factor to consider in protection of ambient air quality.)

Attachment BB: Emission Calculations
 Southwest Materials
 2009-10-049

Description	¹ MHDR	MHDR Units	² PM ₁₀ EF	EF Units	Control Eff. %	Emissions (lb/hr)	³ Modeling Rate (lb/hr)
Aggregate Transfer MC 3.0	94.00	tph	0.00156	lb/ton	N/A	0.15	0.123
Sand Transfer MC 4.17	70.00	tph	0.00099	lb/ton	N/A	0.07	0.058
Cement Unloading to Silo	24.00	tph	0.00034	lb/ton	N/A	0.01	0.007
Supplement Unloading (pneumatic)	4.00	tph	0.00490	lb/ton	N/A	0.02	0.016
Weight Hopper Loading	164.00	tph	0.00075	lb/ton	99.00	0.00	0.001
Truck Mix Unloading	28.00	tph	0.01600	lb/ton	N/A	0.45	0.374
Storage Pile - Load In MC 3	164.00	tph	0.00160	lb/ton	N/A	0.26	0.219
Storage Pile - Load Out MC 3	164.00	tph	0.00160	lb/ton	N/A	0.26	0.219
Storage Pile - Wind Errosion	0.35	acres	0.08917	lb/acre-hr	N/A	0.03	0.026
Storage Pile - Vehicular Activity	0.39	VMT/hr	1.879596	lb/VMT	95.00	0.04	0.030
Haul Road agg/sand/cem/conc	2.53	VMT/hr	1.89870	lb/VMT	95.00	0.24	0.200

¹Maximum Hourly Design Rate (MHDR)

²Emission Factor (EF)

³The Modeling Rate is the emission rate scaled to the daily hours of operation at the MHDR allowed by the permit.

Mr. Jim David
Operations Manager
Southwest Materials
P.O. Box 1165
Branson, MO 65616

RE: New Source Review Permit - Project Number: 2009-10-049

Dear Mr. David:

Enclosed with this letter is your permit to construct. Please study it carefully. Also, note the special conditions, if any, on the accompanying pages. The document entitled, "Review of Application for Authority to Construct," is part of the permit and should be kept with this permit in your files. Operation in accordance with these conditions and your new source review permit application is necessary for continued compliance. The reverse side of your permit certificate has important information concerning standard permit conditions and your rights and obligations under the laws and regulations of the State of Missouri.

If you have any questions regarding this permit, please do not hesitate to contact David Little, at the Department's Air Pollution Control Program, P.O. Box 176, Jefferson City, MO 65102 or at (573) 751-4817. Thank you for your attention to this matter.

Sincerely,

AIR POLLUTION CONTROL PROGRAM

Kendall B. Hale
New Source Review Unit Chief

KBH:dll

Enclosures

c: Southwest Regional Office
PAMS File: 2009-10-049

Permit Number: